

TECHNICAL DATASHEET

PROPAK-FX-EZ-FLO - SELF CONTAINED BREATHING APPARATUS



DESCRIPTION

The Scott Safety ProPak-FX-EZ-FLO is a Type 2 open circuit, self-contained, compressed air breathing apparatus. It consists of a back plate, padded carrying harness and pneumatic system, containing a cylinder connector, reducer, pressure gauge, whistle and demand valve.

The ProPak-FX-EZ-FLO can be configured in a number of different ways with various size single cylinders. There are also a range of variants available including Airline (AC), Split Demand Valve Coupling (SDC or Y2C), Quick Connect Option or Duo variants.

The ProPak-FX-EZ-FLO is used in conjunction with AV3000HT facemask and a choice of composite or steel cylinders.

APPLICATIONS

The ProPak-FX-EZ-FLO is specifically designed as a professional fire fighting SCBA, but is also suitable for providing respiratory protection in any IDLH environment.

Approvals

CE marked in accordance with EN137:2006: Type 2

AS1716

TECHNICAL DATASHEET

Technical Specifications	
Materials	
Pressure Reducing Valve	Nickel Plated Brass
Rust Tube (Cyls)	Brass
Reducing Valve Seat	Polyamide (Nylon)
O-Rings	Nitrile, Silicone, EPDM
Reducing Valve Springs	Stainless Steel
HP Pressure Gauge	Stainless Steel, Polycarbonate Lens
HP Pressure Gauge Cover	Neoprene
MP Air Supply Hose Fittings	Nickel Plated Brass
Facemask	Neoprene, Silicone or Procomp
Facemask Visor	Polycarbonate
MP Air Supply Hose	EPDM Cover, fabric braid reinforcement, EPDM liner
HP Air Hose	PTCFE liner, stainless steel braiding, Estane sleeve
Valve Handwheel (Sabre Cyls)	Glass filled Polyamide/ TPE
Harness	Kevlar and Pyrogard blend webbing with FR Proban covered flame retardant foam. Reflective thread
Backplate	Glass & Carbon filled Nylon composite
Backpad	Flame retardant cross linked polyolefin closed cell foam covered in a Proban fabric
Cylinder Band	Kevlar and Pyrogard blend webbing, Reflective thread
Strap Buckles	Glass filled polyamide
Cylinder	Steel or Composite
Cylinder Valve	Nickel Plated Brass
Demand Valve Casing	Glass filled nylon

MAINTENANCE/CLEANING/SERVICING

N.B. - Cleaning should only be carried out as specified in the user instructions. Maintenance and Servicing must only be performed by trained personnel following the procedures in the Service and Maintenance manual.

TECHNICAL DATASHEET

Technical Specifications	
EZ-Flo Demand Valve	
Ergonomically designed demand valve featuring low breathing resistance, anti fogging spray bar and automatic first breath activation.	
First breath activation	-12.5 to -7.5 mbar
Bypass flow	Variable between 130 to 295 lpm
Reducing Valve	
First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve. Valve body and cap machined from nickel-plated brass with stainless steel spring and hose retainer Uclips.	
Outlet Pressure	
200 bar inlet	5.5 to 9.5 bar
300 bar inlet	6.0 to 11.0 bar
Pressure relief valve protected	Approx. 13.5 bar
Flow restrictor to gauge supply hose	<25 litres minute
Pressure Indicator & Warning Whistle	
Bourdon tube type dial indicator	
Heat and impact resistant Polycarbonate lens	
Safety blow-out vent in rear of gauge	
Accuracy	+/- 10 bar between 40-300 bar
Hoses	
Stainless Steel swivel hose fittings	
Medium Pressure Hose	
Maximum working pressure	16 bar
Minimum burst pressure	80 bar
High Pressure hose	
Maximum working pressure	450 bar
Minimum burst pressure	800 bar
Weight/ Dimensions	
Single configuration (less cylinder)	3.5KG
Single configuration & facemask (less cylinder)	4.5KG
Length	630mm
Width	285mm
Depth (with 6.0 litre 200 bar cylinder)	220mm



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.