

ANALOX

ACG+

looking after the air you breathe



What?

The ACG+ is a unique compressed breathing air monitor designed to be used in a fixed installation near your air compressor or as an ideal portable solution for multi-point air monitoring. The ACG+ offers the user peace of mind as it continually monitors Oxygen (O₂), Carbon Dioxide (CO₂), Carbon Monoxide (CO), dew point (H₂O) and Volatile Organic Compounds (VOC) and also has a sample port to check for oil mist. Continual monitoring or periodic checking of these parameters aids the user in achieving compliance with breathing air standards such as EN12021 and other local regulations, whilst ensuring those employees breathing the air are safeguarded against potentially fatal contamination issues.

Housed in a robust case when used portably or in a purpose built housing when used in a fixed position, the ACG+ is simple to install, use and maintain and has a low cost of ownership. The ACG+ offers 90 days of datalogging, easily retrieved with a usb connection and has audio/visual alarms and a common relay to connect to a beacon or to shut down the compressor should an alarm be triggered.

Why?

Employers have a duty of care to their employees to ensure the air they breathe is of the best quality possible and regulations such as EN12021 require contaminants such as CO and VOCs are maintained at very low levels as they can cause serious health effects, particularly as the effects of such contaminants are increased at pressure.

Even new, well-sited and well-maintained compressors can sometimes fail and contaminants can also enter into the breathing air through the intake. As this can theoretically happen at any time, continual monitoring is a safer and more accurate best practice than "spot checking" such as using colorimetric tube testing kits at intervals.

Where?

The ACG+ can be used with any breathing air compressor and simply needs to be connected after the compressor and before the end user (or cylinder) to ensure that contaminants can be detected before they reach the intended destination. The pressure needs to be regulated down to between 5 to 10 Bar. The ACG+ is most commonly situated in the compressor room but when used portably it can be used in most environments.





looking after the air you breathe

KEY FEATURES


- Portable or fixed
- Mains, DC and up to 12 hour rechargeable battery power options
- Proprietary dew point sensor lock out system for fast start up - ideal for multi point checking
- Proprietary humidifier option for continual use to prolong electrochemical sensor lives (CO & O₂)
- Easy-connect purge system - helps ensure accurate readings in minutes
- Robust carry case
- Sensors now even easier to change out
- NiMH or Lithium battery options
- 90 days of datalogging easily retrieved via USB connection



The ACG+ meets the requirements of the following breathing air standards:



US Navy Dive Manual



SS521-AK-HBK-010

Measurement	Range	Accuracy	Technology
Oxygen	0 to 50%	±(0.035% O ₂ + 1% of reading + 0.15% of reading/°C)	Analox MEC intelligent electrochemical oxygen sensor
Carbon dioxide	0 to 1000ppm	±(25ppm CO ₂ + 1% of reading + 1ppm CO ₂ /°C)	Analox 5S3 intelligent NDIR sensor
VOC	0 to 100ppm	±(1ppm VOC + 5% of reading + 0.25% of reading/°C)	Analox MEC intelligent PID sensor
Carbon monoxide	0 to 20ppm	±(1ppm CO + 5% of reading + 0.1ppm CO/°C + 0.5% of reading/°C)	Analox MEC intelligent electrochemical sensor
Water vapour	0 to 100mg/m ³	±(0.15mg/m ³ H ₂ O + 20% of reading)	Water vapour sensor using capacitive technology

The ACG+ is built upon Analox's latest innovations in sensor technology. The new range of 5S3 and MEC intelligent sensors are Analox's most compact, miniaturised range of sensors to date. Each sensor comes with its own electronics for signal processing and temperature compensation which enables each sensor to become a field replaceable item.

Power Input voltage: 24V DC Power consumption: 24 W (max)
Optional power supply Universal mains adaptor; Input: 95 to 250VAC, 50/60Hz
Sensor response time T ₉₀ < 120 secs T ₉₀ < 15 mins (water vapour sensor)

Flow rate 5LPM (max)
Inlet pressure 5 to 10 bar gauge
Operating temperature -5°C to 50°C
Storage temperature -10°C to 60°C

Humidity 0 to 99% RH (non condensing)
Environmental protection rating IP54
Outputs 1x Normally open relay contacts 1x Normally closed relay contacts 3x 24V DC switched output



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.