



Handheld Thermometers



handheld thermometers

4500 High Accuracy Smart Probe Thermometer



4500
High accuracy smart probe

The Model 4500 Series Ultra-High Accuracy Thermometer take metrology-level temperature measurement to the laboratory, the production floor and the field.

Ultra-high system accuracy, $\pm 0.015^{\circ}\text{C}$, is achieved because the thermometer and probe function as if they were calibrated together as a system even though they can be purchased separately. The 4500 System uses coefficients stored in each probe with the Steinhart-Hart algorithm to calculate the exact temperature reading every time you plug in a probe to take a measurement.

The 4500 series thermometers accept a wide range of plug-in probes equipped with proprietary Smart Probe system. The probes utilize super stable thermistors capable of providing high resolution, fast response and ultra high accuracy.

System Features

- High system accuracy
- NIST traceable calibration included
- Interchangeable temperature probes
- Hand-held flexibility
- Hold reading button
- $^{\circ}\text{C}/^{\circ}\text{F}$ display
- Auto shut off
- Three decimal place mode
- Delta T
- Function keys
- Min/Max reading
- RS-232 serial port

Applications

- Calibrate/verify your PCR Thermal Cycler
- Reference thermometer for your liquid bath
- Clinical laboratory quality control
- Chemical & petroleum regulatory/safety
- Metrology
- Thermal cycler plate uniformity
- Autoclave integrity

Technical Specification

Resolution:	0.01 $^{\circ}\text{C}$ or 0.001 $^{\circ}\text{C}$ selectable 0.001 $^{\circ}\text{C}$ when using serial output
Display:	LCD 4 1/2 digit 0.6" high. Function icons.
Maximum Meter Range:	-40 to +150 $^{\circ}\text{C}$ (-40 to +299 $^{\circ}\text{F}$)
Power:	9 volt Alkaline battery or external 12 VDC. Battery life 25 hours, typical; 15 with RS-232.
Reading Rate:	2 per second (update every 524 milliseconds)
Over Range Indication	Displays LO or HI
Operating conditions	Temperature 0 $^{\circ}\text{C}$ to 45 $^{\circ}\text{C}$ Humidity 0 to 85%

Ordering Information

Product Code	Model Number
FDB4400T	4500 High Accuracy Thermometer



Smart Probes Thermometer

Stainless Steel Tube Probe, for waterbaths, block calibrators & other general purpose use.
Designed for use with the 4500 Thermometer simply plug & play into the 4500 Thermometer.

Technical Specification

Sheath Size:	0.156" (5/32") dia. x 12.0" L
Temperature Range:	-40°C to +150°C
Accuracy*: 0 to 100°C ±0.025°C	-25 to 125°C ±0.05°C
	-40 to 150°C ±0.15°C

*(accuracy specification includes 4500 thermometer)

Ordering Information

Product Code	Model Number	Temperature Range
FDBPR32	4500 5/32" Probe	-40°C to 150°C
FDBPR02	4500 0.2ml Probe	0°C to 100°C
FDBPR05	4500 0.5ml Probe	0°C to 100°C





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.