

Heating oven with mechanical control

With a BINDER E series heating oven, you obtain a reliable and powerful unit in a solid configuration at a very attractive price. This heating oven is preferred for tasks in basic research, as well as in human and veterinary medicine.



Advantages:

- Reliable powerful drying oven
- Very attractive price
- Quality "Made in Germany"

Areas of application:



Basic Research /
Research Institutes



Human / Veterinary
Medicine



Clinics / University
Hospitals

Features

Reliable powerful drying oven

Customer benefits

- Very attractive price

Characteristics

- Quality "Made in Germany"
- Long service life

- Temperature range 60 °C (140 °F) to 230 °C (446 °F)
- Robust, space-saving small unit with hydraulic-mechanical control and adjustable ventilation
- Hydro-mechanical thermostat
- Timer 0 to 120 min
- Optional independent temperature safety device class 1 (DIN 12880)
- 2 chrome-plated racks included
- Units are stackable
- BINDER test confirmation

E 28

▶ Exterior dimensions	
Width (mm)	580
Height (incl. feet) (mm)	405
Depth (mm)	425
Plus door handle, I-panel, connection (mm)	50
Wall clearance, rear (mm)	100
Wall clearance, side (mm)	160
Number of doors (ea.)	1

▶ Interior dimensions	
Width (mm)	400
Height (mm)	280
Depth (mm)	250
Interior volume (l)	28
Racks (number standard/max.)	2 / 4
Load per rack (kg)	10
Permitted total load (kg)	25
Weight (empty) (kg)	22

▶ Temperature data	
Temperature (°C)	60 - 230
Temperature variation at 70 °C (± K) 1)	3
Temperature fluctuation at 70 °C (± K)	1,5
Warm-up time 2)	
at 70 °C (min.)	28
at 150 °C (min.)	36
Recovery time after doors were open for 30 sec. 2)	
at 70 °C (min.)	11
at 150 °C (min.)	19
Ventilation data	
Ventilation at 70 °C (x/h)	30

E 28

▶ Electrical data	
IP protection class acc. to EN 60529	IP 20
Voltage ($\pm 10\%$) 50 / 60 Hz (V)	230
Nominal power (kW)	0,8

1) without a viewing window

2) To 98% of the set value

All technical data are specified for units with standard equipment at an ambient temperature of 25 °C and a line voltage fluctuation of $\pm 10\%$. The temperature data is determined in accordance to factory standard following DIN 12880, respecting the recommended wall clearances of 10% of the height, width and depth of the inner chamber. All figures are typical average values for series devices.

We reserve the right to alter technical specifications at any time.

E 28

Rack, chrome-plated	<input type="radio"/>
Shelf, perforated, stainless steel	<input type="radio"/>



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.