


CB 150 - CO₂ incubator with hot air sterilization

Precision equipment for cell cultivation of the future. It has a drift-free infrared CO₂ measuring system to ensure stable pH values, condensation-free Permadyr™ interior chamber with integrated shelf supports, easy to clean, where the surface area is kept to a minimum in order to reduce potential sites for germs to establish; an effective sterilization program that operates at 180 °C in compliance with standards, for cultivation without any contamination. All of these features along with the absolutely precise temperature accuracy, which you have come to expect from us.



▶ Performance features and equipment :

- Electronically controlled APT.line™ preheating chamber assuring temperature accuracy and reproducible results
- Temperature range 7 °C (13 °F) above ambient temperature up to 60 °C (140 °F)
- MCS controller with 25 storable programs of 100 sections each for a maximum of 500 program segments
- Features:
 - User-friendly LCD screen
 - Easy-to-read menu guide
 - Integrated electronic chart recorder
 - Variety of options for the graphic display of process parameters
 - Real-time clock
- Standard compliant 180 °C (356 °F) hot air sterilization using an overnight cycletime (acc to. DIN 58947, Pharmacopoeias, ANSI)
- VENTAIR™ Jacket System
- Drift free infrared CO₂ measurement system
- Gas mixing head
- Permadyr™ system - condensation-free double-pan humidification system, maintains dry interior walls
- Weldless deep-drawn inner chamber made of stainless steel with integrated shelf support system
- Electronic self-diagnostic system for errors with optical and audible alarm, as well as relay contact for central monitoring
- Independent adjustable temperature safety device class 3.1, providing full protection against chamber over-temperature, with visual and audible temperature alarm
- Tightly-fitting inner glass door
- RS 422 interface for use with optional GMP/GLP and FDA guideline 21 CFR Part 11 compliant APT-COM™ DataControlSystem software
- 3 perforated shelves made of stainless steel (in standard and O₂-control versions)
- Lockable door
- BINDER test certificate



CB 150

Exterior dimensions	
Width (mm/inch)	680 / 26.8
Height (inclusive feet/casters) (mm/inch)	919 / 36.2
Depth (plus 54 mm (2.13 in.) for instrument panel) (mm/in.)	715 / 28.2
Wall clearance side (mm/inch)	54 / 2.1
Interior dimensions	
Width (mm/inch)	500 / 19.7
Height (mm/inch)	600 / 23.6
Depth (mm/inch)	500 / 19.7
Interior volume (l/cu.ft.)	150 / 5.4
Perforated shelves, stainless steel (number standard/max.)	3 / 6
Dimensions of perforated shelves, Width (mm/inch)	495 / 19.5
Dimensions of perforated shelves, Depth (mm/inch)	444 / 17.5
Weight of the unit (empty) (kg/lbs.)	107 / 236
Temperature / CO2 data	
Temperature range 7 °C (13 °F) above ambient up to °C/°F	60 / 140
Temperature variation at 37 °C (98.6 °F) (± °C)	0.3
Temperature fluctuation (± °C)	0,1
Recovery time after door was opened for 30 sec. 1) at 37 °C (98.6 °F) (Min.)	3
CO2-range (Vol.-% CO2)	0-20
Setting accuracy (Vol.-% CO2)	0.1
Recovery time after door was opened for 30 sec. 1) up to 5 Vol.-% (min)	6
CO2-measurement	IR
Connection hose nozzle DN6 for CO2 for hose with internal diameter (mm/inch)	6 / 0.24
Humidity average value (% RH)	95
O2-range (Vol.-% O2)	0.2–95
Setting accuracy (Vol.-% O2)	0.1
Recovery time 1) from 21 vol % up to 0.2 vol % O2 (Min.)	33
from 21 vol % up to 2 vol % O2 (Min.)	19
from 21 vol % up to 5 vol % O2 (Min.)	11
from 21 vol % up to 30 vol % O2 (Min.)	4
O2-measurement	ZrO2
Electrical data	
Housing protection acc. to EN 60529	IP 20
Nominal voltage (±10 %) 50 / 60 Hz (V)	230 / 115
Nominal power (W)	1300
Energy consumption at 37 °C (98.6 °F) (W)	140


1) up to 98 % of the set value

All technical data are specified for units with standard equipment at an ambient temperature of 25 °C and a voltage fluctuation of ±10 %. The temperature data are determined in accordance to factory standard following DIN 12880 respecting the recommended wall clearances of 10 % of the height, width and depth of the inner chamber. All indications are average values, typical for units produced in series. We reserve the right to alter technical specifications at all times.



▶ Gas-tight, divided inner glass door

Maintains consistent climatic conditions within the incubator. Minimal loss of incubator atmosphere, heat and, CO₂ during loading, as well as fast recovery times.



▶ Silicon access ports

Silicon access ports are provided for inserting external measuring devices. They have a diameter of 30 mm and can be sealed with a silicone plug on both sides, for positioning either on the left or the right rear side.



▶ Stacking frame

Used for stacking two BINDER CO₂ Incubators which are thermally isolated from each other.



CB 150

Ethernet interface instead of the RS 422 interface	<input type="radio"/>
Silicone access port closable with two silicone lids, 30 mm back	<input type="radio"/>
Locking of controller keyboard	<input type="radio"/>
Gastank connection kit for CO ₂ , consisting of a gastank pressure regulator, max. pressure 10 bar, with connection parts, and a 5 m hose.	<input type="radio"/>
Gastank connection kit for O ₂ , consisting of a gastank pressure regulator, max. pressure 10 bar, with connection parts, and a 5 m hose.	<input type="radio"/>
Gastank connection kit for N ₂ , consisting of a gastank pressure regulator, max. pressure 10 bar, with connection parts, and a 5 m hose.	<input type="radio"/>
Manual for Primary Human Cell Culture, in English.	<input type="radio"/>
Factory calibration certificate for temperature and CO ₂ . Temperature measurement in center / CO ₂ measurement performed using analyzed test gas at 37 °C (98.6 °F) and 5 % CO ₂ .	<input type="radio"/>
Factory calibration certificate for the O ₂ control option. O ₂ measurement performed using analyzed test gas at 1% O ₂	<input type="radio"/>
Temperature measurement acc. to DIN 12880 (27 measuring points) at 37 °C (98.6 °F) or at specified temperature with measuring protocol and certificate.	<input type="radio"/>
Independent electronic safety system Intelligent Fail Safe. Unique safety plus for continuous monitoring of the CO ₂ control, preventing any unnoticed deviations of the CO ₂ concentration from the set point.	<input type="radio"/>
Gas Supply Control Unit, for the connection of 2 gastank, either CO ₂ or N ₂ , with acoustic and visible alarm. (Available second quarter 2009)	<input type="radio"/>
Silicone access port closable with two silicone lids, 30 mm	<input type="radio"/>
CO ₂ gastank changer, for connecting two gas gastanks. Offers precise control over the current condition of CO ₂ supply to incubator by means of alarm messaging and incident reporting.	<input type="radio"/>
CO ₂ gastank changer, for connecting two gas gastanks, with external connection for up to one additional CO ₂ incubator. Offers precise control over the current condition of CO ₂ supply to incubator by means of alarm messaging and incident reporting.	<input type="radio"/>
O ₂ and N ₂ gastank changer, for all models, for connecting two gastanks of either gas.	<input type="radio"/>
4-20 mA analog output for temperature and CO ₂ measurements (e.g. chart recorder connection), with 6-pin DIN socket (output not adjustable).	<input type="radio"/>
Interior power socket with ON/OFF switch and LEMO connector (maximum power rating 230 V, 1N, 50 / 60 Hz)	<input type="radio"/>
Perforated shelf, stainless steel, suitable for interior chamber with integrated shelf support system (shelf runners)	<input type="radio"/>
Divided shelf, for divided inner glass door (4 doors) stainless steel, suitable for interior chamber with integrated shelf support system (shelf runners)	<input type="radio"/>
Base on castors	<input type="radio"/>
Stacking frame vibration - free, on castors with stop brake, for direct and safe stacking of 2 CB incubators with wedge equipment.	<input type="radio"/>
Stacking adapter for direct thermal decoupled stacking of 2 CB incubators	<input type="radio"/>
Stacking adapter for direct thermal decoupled stacking of a CB 150 / C 150 combination	<input type="radio"/>
CELLROLL. Modular and expandable roller bottle system for cell cultivation. This system is also suitable for the cultivation of adherent cells (e.g. for vaccine production) and suspension cultures.	<input type="radio"/>



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.