

GasAlertClip EXTREME



WATER RESISTANT

Up to three years of continuous maintenance-free protection

Simply press the START/TEST button and the GasAlertClip Extreme is ready to use, providing continuous, reliable protection. Available in two year (H₂S, CO, O₂, SO₂) or three year (H₂S, CO) versions, this single gas detector requires no calibration, sensor replacement, battery replacement or battery charging. Compatible with the MicroDock II automatic test system, the simplicity of the GasAlertClip Extreme combined with minimal training requirements and negligible maintenance costs make the GasAlertClip Extreme one of the most cost-effective gas detection solutions for facility workers and on-site contractors.




H₂S
CO
O₂
SO₂



Standard Package Contents

- Detector complete with specified sensor, stainless steel alligator clip and concussion-proof housing
- Test cap and hose
- Instructions
- Multi-language manual CD

General Specifications

Size	1.1 x 2.0 x 3.2 in. / 2.8 x 5.0 x 8.1 cm
Weight	2.7 oz. / 76 g
Typical battery life	Two years (H ₂ S, CO, SO ₂ or O ₂) or three years (H ₂ S or CO)
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping ATEX: CE  II 1 G Ex ia IIC T4 IECEx: Ex ia IIC T4 INMETRO: BR-Ex ia IIC T4 CE: European Conformity
Warranty	2 or 3 years from activation (given normal operation), plus 1 year shelf life

BW
Technologies
by Honeywell

GasAlertClip Extreme

SINGLE GAS DETECTOR

GasAlertClip Extreme 2-Year Detectors

	Alarm Setpoint	Order Number*
Hydrogen sulfide (H ₂ S)	Low - 10 ppm / High - 15 ppm	GA24XT-H
Hydrogen sulfide (H ₂ S) - bulk pack	Low - 10 ppm / High - 15 ppm	GA24XT-H-B50
Hydrogen sulfide (H ₂ S)	Low - 5 ppm / High - 10 ppm	GA24XT-H510
Carbon monoxide (CO)	Low - 35 ppm / High - 200 ppm	GA24XT-M
Carbon monoxide (CO)	Low - 30 ppm / High - 200 ppm	GA24XT-M30200
Carbon monoxide (CO)	Low - 50 ppm / High - 200 ppm	GA24XT-M50200
Sulfur dioxide (SO ₂)	Low - 5 ppm / High - 10 ppm	GA24XT-S
Oxygen (O ₂)	Low - 19.5% / High - 23.5%	GA24XT-X
Oxygen (O ₂)	Low - 19.5% / High - 22.5%	GA24XT-X19.522.5
To order a 50-unit bulk package (one model type per pack only)		Add Suffix "-B50"

GasAlertClip Extreme 3-Year Detectors

	Alarm Setpoint	Order Number*
Hydrogen sulfide (H ₂ S)	Low - 10 ppm / High - 15 ppm	GA36XT-H
Hydrogen sulfide (H ₂ S)	Low - 5 ppm / High - 10 ppm	GA36XT-H510
Carbon monoxide (CO)	Low - 35 ppm / High - 200 ppm	GA36XT-M
Carbon monoxide (CO)	Low - 30 ppm / High - 200 ppm	GA36XT-M30200
Carbon monoxide (CO)	Low - 50 ppm / High - 200 ppm	GA36XT-M50200
To order a 50-unit bulk package (one model type per pack only)		Add Suffix "-B50"

Note: Customer specified alarm settings are available for orders with a minimum quantity of ten (10) units.

* Add "-BR" to the end of the order number for INMETRO certified detectors (for Brazil only).



Bulk Package

Bulk packaging is the environmentally friendly choice for easy distribution and space efficiency. (Add suffix "-B50" for 50-unit bulk package.)

Carrying Accessories	Order Number
Concussion-proof boot with stainless steel alligator-style clip	GA24-BALERT
Splash guard filters, kit of 5 for use with concussion-proof boot (GA24-BALERT)	GA-BSPLASH-K
Belt clip with screw	GA-CL-1
Hard hat clip (non-conductive)	GA-HC-1
Alligator-style clip (non-conductive)	GA-AG-1
Alligator-style clip (stainless steel)	GA-AG-2
Neck strap with safety release	GA-NS-1
Short strap (6 in./15.2 cm)	GA-LY-1
Extension strap (4 ft./1.2 m)	GA-ES-1
Armband	GA-ARM-1

Event Logging Accessories	Order Number
IR DataLink USB adaptor	GA-USB2

Testing Equipment and Spares	Order Number
Test cap and hose (1 ft./0.3 m) replacement (included with detector)	GA-TC-1

MicroDock II automatic test and calibration system base station and GasAlertClip Extreme docking module	
- H ₂ S (hydrogen sulfide)	DOCK2-2-1E-00-N*
- SO ₂ (sulfur dioxide)	DOCK2-2-1F-00-N*
- CO (carbon monoxide)	DOCK2-2-1G-00-N*
- O ₂ (oxygen)	DOCK2-2-1H-00-N*
GasAlertClip Extreme MicroDock II docking module	
- H ₂ S (hydrogen sulfide)	DOCK2-0-1E-00-N
- SO ₂ (sulfur dioxide)	DOCK2-0-1F-00-N
- CO (carbon monoxide)	DOCK2-0-1G-00-N
- O ₂ (oxygen)	DOCK2-0-1H-00-N

For complete MicroDock II system configuration information, see MicroDock II section.

*Change order number suffix "-N" to: "-E" for European versions, "-U" for United Kingdom versions, "-A" for Australian versions.



MicroDock II
Automatic test and calibration station (see MicroDock II section for additional information)





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.