4-gas detector with pump

H₂S

CO

 O_2

LEL

GasAlert T





General Specifications		
Size	5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm	
Weight	11.1 oz. / 316 g	
Typical battery life	13 hours @ 32°F / 0°C 10 hours @ -4°F / -20°C Recharges in 6 hours	
Certifications and approvals	ATEX: IECEx: INMETRO: (€:	Class I, Div. 1, Gr. A, B, C, D C € ⊕ II 1 G Ga Ex ia IIC T4 Ga Ex ia IIC T4 BR-Ex ia IIC T4 European Conformity
Warranty	Full 2-year warranty including all sensors	

Simple operation with pump

The rugged GasAlertMax XT reliably monitors for up to four gas hazards and combines straightforward one-button field operation with an integrated sampling pump. Tamper-proof, user-adjustable options enable the instrument to be customized to suit your application. Confined space entry and remote sampling have never been so easy with new, intelligent SmartSample pump technology. Minimize pump blockages and improve remote sampling result accuracy. Powered by a rechargeable battery pack that provides runtime for an entire 13 hour shift, the compact GasAlertMax XT comes with standard event logging and datalogging. The GasAlertMax XT is fully compatible with the MicroDock II automated test and calibration system.







Standard Package Contents

- Detector complete with specified sensor(s), stainless steel alligator clip and concussion-proof housing
- Rechargeable lithium polymer battery
- Charging adaptor
- 3 ft./1 m calibration hose with quick connect
- 10 ft./3 m sampling hose with particulate filter and guick connect
- Reversible screwdriver
- Kit of 5 spare pump filter
- Manual
- Multi-language manual CD



Order Number

GasAlertMax XT 4-Gas Detector	Yellow	Black
%LEL, O ₂ , H ₂ S, CO	XT-XWHM-Y-NA	XT-XWHM-B-NA

GasAlertMax XT 3-Gas Detector	Yellow	Black
%LEL, O ₂ . H ₂ S	XT-XWH0-Y-NA	XT-XWH0-B-NA
%LEL, O ₂ , CO	XT-XW0M-Y-NA	XT-XW0M-B-NA
O ₂ , H ₂ S, CO	XT-X0HM-Y-NA	XT-X0HM-B-NA
%LEL, H ₂ S, CO	XT-0WHM-Y-NA	XT-0WHM-B-NA

GasAlertMax XT 2-Gas Detector	Yellow	Black
%LEL, O ₂	XT-XW00-Y-NA	XT-XW00-B-NA
H ₂ S, CO	XT-00HM-Y-NA	XT-00HM-B-NA
O ₂ , H ₂ S	XT-X0H0-Y-NA	XT-X0H0-B-NA
O ₂ , CO	XT-X00M-Y-NA	XT-X00M-B-NA
%LEL, H ₂ S	XT-0WH0-Y-NA	XT-0WH0-B-NA
%LEL, CO	XT-0W0M-Y-NA	XT-0W0M-B-NA

GasAlertMax XT 1-Gas Detector	Yellow	Black
O ₂	XT-X000-Y-NA	XT-X000-B-NA
%LEL	XT-0W00-Y-NA	XT-0W00-B-NA
H ₂ S	XT-00H0-Y-NA	XT-00H0-B-NA
CO	XT-000M-Y-NA	XT-000M-B-NA

GasAlertMax XT Region Codes

For orders outside North America, change order number suffix "-NA" to:			
"-EU"	Europe	"-BR"	Brazil
"-UK"	United Kingdom	"-OR"	Other region with 3-pin UK plug
"-AU"	Australia	"-OE"	Other region with 2-pin UK plug
"-CN"	China/New Zealand		





MicroDock II
Automatic test and calibration station
(see MicroDock II section for additional information)

Gas Legend

Ous Legenu		
%LEL	Combustible	
O ₂	Oxygen	
H_2S	Hydrogen sulfide	
CO	Carbon monoxide	

Confined Space Kit	Order Number
GasAlertMax XT deluxe confined space kit Detector and calibration gas sold separately	XT-CK-DL
Carrying case for GasAlertMax XT with foam insert	XT-CK-CC

Carrying Accessories	Order Number
Concussion-proof boot with stainless steel alligator-style clip	GA-BXT
Carrying holster for detector and sampling hose	GA-HXT
Neck strap with safety release	GA-NS-1
Extension strap (4 ft./1.2 m)	GA-ES-1
Short strap (6 in./15.2 cm)	GA-LY-1
Armband	GA-ARM-1
Chest harness	GA-CH-2

Power Options and Spares	Order Number
Multi-unit (5) cradle charger	XT-C01-MC5
Multi-unit power adaptor	GA-PA-1-MC5*
12-24 Vpc vehicle power adaptor	GA-VPA-1
12-24 Vpc direct-wire power adaptor	GA-PA-3
Replacement power adaptor	GA-PA-1-NA**

^{*}For regions outside North America add to the end of the order number: "-EU" for Europe, "-UK" for United Kingdom and "-AU" for Australia/China.

^{**}For regions outside North America replace "-NA" with: "-EU" for Europe, "-UK" for United Kingdom and "-AU" for Australia/China.



Concussion-Proof Boot GA-BXT



Carrying Holster GA-HXT **Sampling Probe** GA-PROB1-1



Multi-Unit Cradle Charger XT-C01-MC5 Simultaneously charge 5 detectors



Multi-Unit Power AdaptorGA-PA-1-MC5
Simultaneously charge 5 detectors



Vehicle Power Adaptor 12-24 Vbc GA-VPA-1



Direct-Wire Power Adaptor
12-24 Vbc
GA-PA-3
Used for emergency vehicles
and other applications



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.

UK Office Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560 Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.