

Electrothermal Paraffin Wax Dispenser

The Electrothermal Paraffin Wax Dispenser provides immediate “Wax On Tap” for Pathology laboratories etc.



The problem of wax solidifying at the tap is completely eliminated by the incorporation of a thermally insulated tap heater with independent temperature control.

Capacity:

- 4.5 litres (1 gallon)

Temperature:

- Ambient to 75°C.
- Fitted with safety over-temperature cut-out at 105°C and non-resettable thermal fuse.

Temperature Control:

- A built-in thermostat provides temperature control from ambient 75°C.
- Tap Heater maintains temperature within the tap, keeping the wax molten.

Tap:

- Swivel lever non-drip with replaceable filter

Warranty: One year, parts and labour

Certifications: CE

| Specifications | | |
|---------------------------------|--|-------------------------------|
| Material | Stove Painted Aluminium Case | |
| Max. Element Temperature | 5°C to 40°C. Humidity not to exceed 80%. | |
| Cat. No. | Capacity | Electrical Requirement |
| MH8523B | 4.5 litres (1 gallon) | 230V 50/60Hz |
| MH8523BX1 | 4.5 litres (1 gallon) | 115v 50/60Hz |
| MH8523BX6 | 4.5 litres (1 gallon) | 230v 50/60Hz, EU Plug |



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.