

Electrothermal Multi-Position Stirrers with Individual Speed Control



Electrothermal Multi-Position Stirrers offer six individually controlled stirring positions.

These multi-position stirrers control multiple experiments with varied speeds from 350 to 2000 rpm

- Low-profile design is stable and easy to clean
- Each position is controlled independently using external controller
- Material is moulded ABS (high impact)
- Operating temperature: 0 to 40 C, 0-50% humidity (non-condensing)

Includes: Stirrer, external controller, and 1 stir bar for each position

Warranty: Three years

Certifications: CE

Specifications	
No. of Stirring Positions	6
Capacity	250ml per position
Dimensions, L x W x H	16.5 x 25 x 6.3 cm (6.5 x 9.8 x 2.5 in)
Weight	2.5kg (5.5lb)
Cat. No	Electrical Requirements
PS60087	230V/ UK
PS60087X1	115V/ US
PS60087X6	230V/EU



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.