

CS SERIES TEMPERATURE CALIBRATION SOURCES

A simple to use, cost effective system for on site/laboratory calibration of **BOTH** contact and non-contact (infrared) thermometers, to adhere to quality standards such as ISO9000 and HACCP.



CS174 with RT162 & PC Temp PT2 portable thermometers
CS Series Dimensions (l x w x h) 196 x 174 x 179mm



CS174-IN version rear view showing removable insert
CS174 front view with black body cover removed

- The CS Series comprises of three dry block calibration sources with a “black body” for infrared thermometers & holes for probe thermometers. The units utilise a temperature control system and also feature a pocket for a reference thermometer.
- Model CS173 features a range of +30.0 to +200.0°C and models CS174 & CS175 feature a range of 40°C below the ambient temperature (approx. -20.0°C) to +85.0°C. All models display temperature in °C or °F and include RS232 output as standard and option for USB.
- The CS174 & CS175 are also available with removable inserts – supplied with one insert with standard holes and one “blank” to be configured as required. Use reference CS174-IN & CS175-IN.
- Standard probe hole dimensions: 1 x 2.0mm; 3 x 3.50 mm; 2 x 5.50 mm; 1 x 8.50 mm; depth 77mm. Black body dimensions 73mm x Ø 32mm.
- Calibration certificate traceable to national standards is supplied with all models. Key switch operated precision accuracy check function (PAC) available as an optional extra.

Specification	CS173	CS174/CS174-IN*	CS175/CS175-IN*
Range	+ 30.0 to + 200.0 °C	40.0°C below ambient to +85.0°C	40.0°C below ambient to +85.0°C
Resolution	0.1 °C	0.1°C	0.01°C
Accuracy	± 0.2 °C ± 1 Digit	± 0.2 °C ± 1 Digit	± 0.05 °C ± 1 Digit
Emissivity	> 0.95	> 0.95	> 0.95
Stability	Better than 0.03 °C	Better than 0.03 °C	Better than 0.03 °C
Heating time (typical)	30 to 150°C, 15 mins	20 to 60°C, 6 mins	20 to 60°C, 6 mins
Cooling time (typical)	Non-forced	20 to 0°C, 7 mins	20 to 0°C, 7 mins
Power supply	110V or 220 VAC	100V to 240 VAC	100V to 240 VAC
Operating temp.	0 - 50°C	0 - 50°C	0 - 50°C
Weight (instrument)	4 Kg	4.2 Kg	4.2 Kg

***Includes: 1 x removable insert with standard probe holes & 1 x solid non-drilled insert**

UK 3 pin plug to IEC mains cable supplied as standard. Continental two pin plug available – please specify when ordering

**Contact the sales department and ask for information on complementary instrumentation from Eurolec.
E.g. Portable thermometers (contact and infrared) and manometers.**

Eurolec Instrumentation Ltd are continuously developing and improving their products and as such the company reserve the right to amend specifications without notice and supply products which differ from those described.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.