



Landfill

Gas Extraction

Site Investigation

Landfill Fires

## H<sub>2</sub> Compensated CO Landfill Gas Analyser

The GA 2000 Plus Utilises new technology to give more reliable readings for Carbon Monoxide (CO), helping determine the Presence of fires on Landfill. It incorporates the existing technology and features of the industry standard GA 2000.

### Benefits

- Simultaneous display of all gases
- Easier routine monitoring
- Increased reliability of data
- All routes uploaded for daily routine
- Field proven
- Improved traceability of data
- Easy transfer of data

### Features

- ATEX certified
- 6 gas capacity
- H<sub>2</sub> compensated CO reading
- Peak CH<sub>4</sub> and CO<sub>2</sub>
- Minimum O<sub>2</sub>
- Optional Internal Flow
- Optional Event Log
- CO Alarm
- Stores 2000 Readings and 1000 Ids

### Applications

- Landfill sites
- Brownfield
- Site investigation
- Biogas



# The GA2000 Plus



## GAMS Software

GAMS (Gas Analyser Management Software) enables users to maximise the operation of their gas analyser. It enables both direct and remote communication with the unit. It features a simple upload and download facility and is fully compatible with the latest Microsoft<sup>TM</sup> operating Systems.

## Product Specifications

Gases Measured	CH <sub>4</sub> , CO <sub>2</sub> , by dual wavelength infrared cell with reference channel. O <sub>2</sub> by internal electrochemical cell
----------------	----------------------------------------------------------------------------------------------------------------------------------------------

### Range

CH <sub>4</sub>	0-100% Reading	CO	0-2000ppm (H <sub>2</sub> Compensated)
CO <sub>2</sub>	0-100% Reading	H <sub>2</sub> S	0-500ppm
O <sub>2</sub>	0-25%		

### Gas Accuracy\*

	CH <sub>4</sub>	CO <sub>2</sub>	O <sub>2</sub>
0-5%	±0.5%	±0.5%	±1.0%
5-15%	±1.0%	±1.0%	±1.0%
15% - Full Scale	±3.0%	±3.0%	±1.0%

\* With proper field calibration

### Other Parameters

	Unit	Resolution/Range	Comments
Pressure	mbar	+/- 500 mbar	Direct Measurement

Operating Temperature Range	0°C - 40°C
Relative Humidity	0-95% non condensing
Barometric Pressure Range	±200 mbar from calibration Pressure
Barometric Pressure Accuracy	±5 mbar
Battery Life	Typical use 10 hours from fully charged
Charge Time	Approximately 2 hours from complete discharge
Weight	Approximately 2kg
Dimensions	Length 252mm, Width 190mm, Depth 63mm
Recommended Field Calibration Gas Mix	60% CH <sub>4</sub> / 40% CO <sub>2</sub> or 5% CH <sub>4</sub> , 5% CO <sub>2</sub> , 6% O <sub>2</sub> (dependent on application)



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.