

CH3-150 Combitherm-2 dry block heating/cooling system

Durable compact dry block heating and cooling system with independently regulated heating and cooling blocks in the same unit.

- **Stability:** $\pm 0.1^{\circ}\text{C}$
- **Digital timer with sound alarm:** 1 min to 99 h 59 min
- **User adjustable programs temperature and time:** 16 (heating) and 16 (cooling)
- **Digital temperature control for optimum precision**
- **Independently regulated heating and cooling blocks in the same unit**
- **Temperature Calibration Function**



- Simple programming** for independent use of heating and cooling block.
- Choice of 7 interchangeable blocks** (order blocks separately) - extraction tool supplied as standard. Custom blocks available on request.
- Independent controls** with 16 user adjustable programs including temperature and time.




- Protective lid** - reduces risk of contamination.
- Temperature Calibration Function** for precise temperature control.
- 2 line LCD display** of set and actual parameters to monitor temperature in real-time.
- Easy change of parameters during unit performance** saves time during applications.

Applications

- Life-science - storing restriction enzymes, nick translation, ligation reactions, restriction digests, protein solubilisation for PAGE, warm incubation of microcentrifuge tubes for hybridisation, enzyme reactions and deactivations
- Clinical - cooling blood samples prior to coagulation testing. acylcarnitines derivatisation, MRSA and PBP2 latex testing, heating flush/media used in egg recovery, fertility to keep test tubes at correct temperature during egg collection
- Incubating samples at set temperatures, heating block for boiling of solutions in tubes
- Life-science-cell digestion, DNA/RNA extraction, post sequencing PCT clean-up-dry down step, boiling in vitro DNA RNA/ protein samples, incubating invitro reactions/digestions, extraction of DNA for real-time PCR analysis, denaturing nucleic acid and protein samples
- Industrial - digestion of environmental samples for chemical oxygen demand analysis, soil digests, maintaining temperatures

Dry blocks for heating and cooling - Technical specifications

		Combitherm-2 dry block heating/cooling system	
		CH3-150	
			
Dimensions	h x d x w mm	220 x 285 x 295	
Heating block temperature range	°C	+25 to +150	
Heating block temperature control range	°C	Ambient +5 to +150	
Heating block setting resolution	°C	1	
Heating block stability	°C	±0.1	
Cooling block temperature range	°C	-3 to +20	
Cooling block temperature control range	°C	Ambient -23 to ambient -5	
Cooling block setting resolution	°C	0.1	
Cooling block stability	°C	±0.1	
Digital timer with sound alarm		1 min–99 hrs 59 min (increment 1 min)	
User adjustable programs (temperature and time)		16 (heating) + 16 (cooling)	
Display		LCD	
Nominal operating voltage	V	230 only (50/60Hz)	
Weight	kg	5.6	

Options and accessories

• = optional

B2-50		Interchangeable block for 2 x Ø 48mm tubes depth 58mm
B10-13		Interchangeable block for 10 x Ø 13mm tubes, flat bottom depth 30mm
B10-16		Interchangeable block for 10 x Ø 16mm tubes depth 56mm
B5-29		Interchangeable block for 5 x Ø 29mm tubes, flat bottom depth 40mm
B6-25		Interchangeable block for 6 x Ø 25mm tubes depth 40mm
B18-12		Interchangeable block for 18 x Ø 12mm tubes, round bottom depth 58mm
B23-1.5		Interchangeable block for 23 x 1.5ml micro tubes



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.