

SUB Aqua Pro - 2L, 2L shallow, 5L, 12L, 18L, 26L, 34L and dual

NEW

- PERFORMANCE** › Set and Forget™ technology - fast heat-up, accurate temperature control
- PRECISION** › Excellent temperature stability - $\pm 0.2^{\circ}\text{C}$
- QUALITY** › 3 year warranty. UK design and manufacture
- PROTECT** › User-defined high-temperature alarm & cut-out - protects samples
- CONVENIENT** › Drain tap, tray and lid included
- OPTIMISED** › Heater mat technology - optimised work space and easy to clean
- VALUE** › Advanced dry start and run dry protection - prevents costly service repairs
- ENHANCED** › 3 programmable presets, countdown timer, 2 point calibration,



3
year warranty











Applications

- University - research, sample preparation
- Healthcare - warming samples
- Industry - QA/QC samples
- Pharma/biotech - sample preparation

Ideal choice for University research and Pharma/Biotech

Specifications

	SAP2	SAP2S	SAP5	SAP12	SAP18	SAP26	SAP34	SAPD
								
	2.5 kg l: 200mm w: 185 mm h: 200 mm	3 kg l: 215 mm w: 335 mm h: 150mm	3 kg l: 215 mm w: 335 mm h: 200 mm	6 kg l: 380 mm w: 360 mm h: 225 mm	9 kg l: 590 mm w: 335 mm h: 275 mm	9 kg l: 590 mm w: 335 mm h: 275 mm	14.5 kg l: 770mm w: 335 mm h: 370 mm	9 kg l: 380 mm w: 545 mm h: 225 mm
Capacity	2L	2L shallow	5L	12L	18L	26L	34L	5L & 12L
Temperature range	ambient +5 to 99°C							
Temperature display and setting resolution	0.1°C							
Stability (DIN 12876-3 @70 °C)	± 0.2°C							
Working dimensions (mm)	125 x 140 x 115	145 x 290 x 300	145 x 290 x 115	315 x 290 x 115	495 x 290 x 115	495 x 290 x 165	630 x 290 x 160	145 x 290 x 115 & 315 x 290 x 115
User defined calibration points	2							
Drain tap	-	-	-	●	●	●	●	●
Heater power 230V/120V (kW)	0.25/0.25	0.35/0.35	0.35/0.35	0.8/0.8	1.4/1.05	1.4/1.05	1.8/1.3	1.15/1.15
Supply voltage (V)	120 or 230 (50-60Hz)							



Essential accessories (full range available on website)

Flat lid with ring sets

Variable hole diameter to accommodate tall vessels whilst reducing evaporation



Polypropylene spheres

Useful alternative to a lid, minimises evaporation and heat loss whilst allowing easy access to vessels in the bath; particularly useful for tall vessels



Test tube racks

Stainless steel - range of sizes available for 0.5 to 1.5 ml micro-tubes or 10 to 30 mm tubes



Raised shelves

Stainless steel - shelf covers half area of bath. Reversible, allows two shelf depths



Alternative water bath ranges:



JB Nova - general purpose

- Includes clear polycarbonate lid
- 4 bath sizes: 5L, 12L, 18L, 26L
- Drain tap on 12L, 18L and 26L baths

JB Academy - basic

- Simple and practical, great value
- 3 bath sizes: 5L, 12L, 18L





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.