

FMC-40

1-4 Channel Gas Alarm

The FMC-40 has been designed to operate in the full range of environments from commercial premises through to heavy industrial applications which may require hazardous area sensing.

The FMC-40 system operates on single channels plug and play cards.

Key Features

- Versatile System Configuration
- Flammable, Oxygen and Toxic Gases
- 1 to 4 sensors
- Plug in sensor channel cards
- Two alarm stages
- Selectable alarm relays
- Analogue 4-20mA output
- Delay to alarm option

Applications

- Steel mills
- Waste water
- LGP storage
- Paint spay booths
- Chemical plants
- Chemical storage
- Aircraft hangars
- Boiler rooms







Specifications*

Sensor points	1 ~ 4
Measurements	Combustible Gas - L.E.L., % vol, ppm Toxic Gas - ppm, % vol Oxygen - % vol Depletion/Enrichment Any 4~20mA input signal
Power supply	230/115v AC or 24v DC and specials
Power Consumption	12 watts - full alarm
Indicators	Power - Green L.E.D Mains Fail - power indicator change green to amber Alarms - Red L.E.D.s Fault - Amber L.E.D Digital Display - 3 ¹ / ₂ Digit - gas readout Sensor channel selection indicator - Amber L.E.D System test - Alarm L.E.D.s flashing Alarm Relay Inhibit - Fault L.E.D on
Outputs	High Alarm Relay - Common D.P.C.O Normally energised or de-energised, latched or unlatched Low Alarm Relay - Common D.P.C.O Normally energised or de-energised, latched or unlatched Fault Alarm Relay - Common S.P.C.O Normally energised or de-energised Channel Relays - 1 per channel high or low selectable S.P.C.O Normally energised or de-energised, latched or unlatched General Alarm Relay - resettable S.P.C.O All contacts rated 5A-230vAC Analogue 4 ~ 20mA output per channel Output 24vDC @ 100mA max - auxiliary equipment (non inductive)
Audible Alarm	Permanent mute option. Lo, Hi, Fault alarms
Alarm Settings	Digital Setting (fully adjustable between zero and fullscale) Delay to alarm T1 - 10 seconds, T2 - 30 seconds, T1 + T2 - 10 minutes
Sensor inputs	Bridge type 3 wire mV input 4~20mA (electrochemical/infrared)
Sensor cable	3 core 1.5mm ² screened < 1.5km
Miscellaneous	EMC approvals EN50270 Marine EN60945 Enclosure - cable entry - bottom/rear Operating temperature -10 to +50°C Relative Humidity 0 - 90% Protection IP52 - option IP65 Dimensions 310W x 265H x 75Dmm / 12.2W x 10.4H x 3.0D" Weight 3.6kg / 7.94 lbs. Optional backup battery Field terminals - 2.5mm quick release System/lamp test Remote Accept/Reset Alarm isolate during service - inhibit

*Specifications are subject to change

Field terminals



Repeated for each channel 1~4 terminals 14-21

Configuration options

- Controller module F05-0021-000
- Controller IP 65 option F05-0022-000
- Alarm card for 4-20mA transmitters F05-3021-000
- Battery back up 1 hour F05-3022-000



The FMC-40 includes

- FMC-40
- Channel cards as specified
- Instruction manual



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.