

GasAlert EXTREME



**WATER
RESISTANT**

General Specifications

Size	1.1 x 2.0 x 3.75 in. / 2.8 x 5.0 x 9.5 cm
Weight	2.9 oz. / 82 g
Typical battery life	2 year battery life (typical) with replaceable 3V battery
Certifications and approvals	<ul style="list-style-type: none"> Class I, Div. 1, Gr. A, B, C, D Class II, Div. 1, Gr. E, F, G American Bureau of Shipping ATEX: CE II 1 G Ex ia IIC T4 IECEX: Ex ia IIC T4 INMETRO: BR-Ex ia IIC T4 CE: European Conformity
Warranty	Full 2 year warranty including sensors (1 year Cl ₂ , NH ₃ , O ₃ , ETO & ClO ₂ sensor)

Long-term solution

Compact and affordable, the GasAlert Extreme reliably monitors for any single gas hazard within its wide range of available toxic gas models. With easy on/off operation, this single gas detector offers extended longevity with a two year field-replaceable battery and sensor. A wide range of tamperproof user options and multi-language display make the GasAlert Extreme an ideal solution for a variety of applications; plus, datalogging is now standard on all units. Calibration is a simple automatic procedure and is compatible with BW's MicroDock II automatic test and calibration system.



Standard Package Contents

- Detector complete with specified sensor, stainless steel alligator clip and concussion-proof housing
- Calibration/test cap and hose
- Manual
- Multi-language manual CD

BW
Technologies
by Honeywell

GasAlert Extreme	Measuring Range	Order Number*	
		Yellow	Black
Hydrogen sulfide (H ₂ S)	0-100 ppm	GAXT-H-DL	GAXT-H-DL-B
Hydrogen sulfide (H ₂ S) (extended range)	0-500 ppm	GAXT-H-2-DL	GAXT-H-2-DL-B
Carbon monoxide (CO)	0-1000 ppm	GAXT-M-DL	GAXT-M-DL-B
Carbon monoxide (CO) (H ₂ resistant)	0-1000 ppm	GAXT-M2-DL	GAXT-M2-DL-B
Oxygen (O ₂)	0-30.0%	GAXT-X-DL	GAXT-X-DL-B
Sulfur dioxide (SO ₂)	0-100 ppm	GAXT-S-DL	GAXT-S-DL-B
Chlorine (Cl ₂)	0-50.0 ppm	GAXT-C-DL	GAXT-C-DL-B
Hydrogen cyanide (HCN)	0-30.0 ppm	GAXT-Z-DL	GAXT-Z-DL-B
Nitrogen dioxide (NO ₂)	0-99.9 ppm	GAXT-D-DL	GAXT-D-DL-B
Ammonia (NH ₃)	0-100 ppm	GAXT-A-DL	GAXT-A-DL-B
Ammonia (NH ₃) (extended range)	0-400 ppm	GAXT-A2-DL	GAXT-A2-DL-B
Phosphine (PH ₃)	0-5.0 ppm	GAXT-P-DL	GAXT-P-DL-B
Ozone (O ₃)	0-1 ppm	GAXT-G-DL	GAXT-G-DL-B
Ethylene oxide (ETO) (C ₂ H ₄ O)	0-100 ppm	GAXT-E-DL	GAXT-E-DL-B
Nitric oxide (NO)	0-250 ppm	GAXT-N-DL	GAXT-N-DL-B
Chlorine dioxide (ClO ₂)	0-1 ppm	GAXT-V-DL	GAXT-V-DL-B

Note: Download of datalogged information requires use of the GA-USB2 high-speed IR adaptor. Receive a GA-USB2 IR DataLink USB Adaptor at no charge with purchase of 10 or more GasAlert Extreme detectors.

**Add "-BR" to the end of the order number for INMETRO certified detectors (for Brazil only).*



IR DataLink
GA-USB2
USB Adaptor



MicroDock II
Automatic test and calibration
station (see MicroDock II section
for additional information)



Gas Legend

Cl ₂	Chlorine	NO	Nitric oxide
ClO ₂	Chlorine dioxide	NO ₂	Nitrogen dioxide
CO	Carbon monoxide	O ₂	Oxygen
ETO	Ethylene oxide (C ₂ H ₄ O)	O ₃	Ozone
H ₂ S	Hydrogen sulfide	PH ₃	Phosphine
HCN	Hydrogen cyanide	SO ₂	Sulfur dioxide
NH ₃	Ammonia		

Carrying Accessories

	Order Number
Concussion-proof boot with stainless steel alligator-style clip	GA-BALERT
Splash guard filters, kit of 5 for use with concussion-proof boot (GA-BALERT)	GA-BSPLASH-K
Hard hat clip (non-conductive)	GA-HC-1
Alligator-style clip (non-conductive)	GA-AG-1
Alligator-style clip (stainless steel)	GA-AG-2
Belt clip with screw	GA-CL-1
Neck strap with safety release	GA-NS-1
Short strap (6 in./15.2 cm)	GA-LY-1
Extension strap (4 ft./1.2 m)	GA-ES-1
Armband	GA-ARM-1
Chest harness	GA-CH-2
Hard-sided carrying case for motorized sampling pump and/or the detector	SPAK-CC1

Datalogging Accessories and Spares

	Order Number
IR DataLink USB adaptor	GA-USB2
<i>Receive a free adaptor with purchase of 10 or more GasAlert Extreme detectors. This high speed adaptor is required to download information from a GasAlert Extreme.</i>	

Sampling/Testing Equipment and Spares

	Order Number
Test cap and hose (1 ft./0.3 m) replacement (included with detector)	GA-TC-1
MicroDock II automatic test and calibration system (Not compatible with ClO ₂ or O ₃)	
- Base station plus GasAlert Extreme docking module	DOCK2-2-1D-00-N*
- GasAlert Extreme module	DOCK2-0-1D-00-N
<i>For complete MicroDock II system configuration information, see MicroDock II section.</i>	
SamplerPak motorized sampling pack kit	GA-SPAK
<i>For a complete list of SamplerPak probes, hoses, accessories and spares, see SamplerPak section.</i>	
Manual aspirator pump kit with probe (1 ft./0.3 m)	GA-AS02

* Change order number suffix "-N" to: "-E" for European versions, "-U" for United Kingdom versions, "-A" for Australian versions.



Concussion-Proof Boot
GA-BALERT



Splash Guard Filters
GA-BSPLASH-K
For concussion-proof boot



Short Strap
GA-LY-1



Armband
GA-ARM-1



Neck strap
GA-NS-1



Test Cap Replacement
GA-TC-1

Power Spares

Battery - lithium, 3V

Order Number

E2829

Sensor Spares and Replacements

Replacement sensor screens with gasket, kit of 10

GAXT-SS

Replacement hydrogen sulfide (H₂S) sensor

PS-RH04S

Replacement carbon monoxide (CO) sensor

PS-RM04

Replacement carbon monoxide (CO) sensor, H₂ resistant

PS-RM04H

Replacement oxygen (O₂) sensor

SR-X10

Replacement sulfur dioxide (SO₂) sensor

PS-RS04

Replacement chlorine (Cl₂) sensor

PS-RC10

Replacement hydrogen cyanide (HCN) sensor

PS-RZ10

Replacement nitric oxide (NO) sensor

SR-N04

Replacement nitrogen dioxide (NO₂) sensor

PS-RD04

Replacement ammonia (NH₃) sensor

SR-A04

Replacement ammonia (NH₃) sensor, extended range

SR-A204

Replacement phosphine (PH₃) sensor

SR-P04

Replacement ozone (O₃) sensor

SR-G04

Replacement ethylene oxide (ETO) sensor

SR-E04

Replacement chlorine dioxide (ClO₂) sensor

SR-V04



SamplerPak Kits

Kits come with motorized sampling pump, batteries, battery charger (if specified) and room for detector (order detector separately); see SamplerPak section for kit contents, accessories and spares



Manual Aspirator Pump

GA-AS02

Complete with probe, hose, aspirator pump and adaptor cap



Sensor Screens

GAXT-SS



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.