

GasAlertMicro 5 Series



WATER RESISTANT

Standard Package Contents

- Detector complete with specified sensor(s), stainless steel alligator clip and concussion-proof housing
- Specified battery option
- Charging adaptor (with rechargeable battery option)
- Screwdriver
- Calibration/test adaptor and hose
- Manual
- Multi-language manual CD

Protect yourself

Compact and lightweight, GasAlertMicro 5 Series instruments are available in diffusion or pumped instruments. Each of the portable gas detectors simultaneously monitors and displays up to five potential atmospheric hazards. The GasAlertMicro 5 PID model also identifies PID detectable VOCs, while the GasAlertMicro 5 IR uses an NDIR sensor to monitor CO₂ levels. Adaptable to a variety of applications, GasAlertMicro 5 Series instruments have an extensive selection of user-settable field options. Use the passcode function to prevent unauthorized modifications of the instrument's settings. Compatible with BW's MicroDock II automatic test and calibration system, the GasAlertMicro 5 is unparalleled in its versatility, performance and overall value.



- VOCs
- CO₂
- LEL
- H₂S
- CO
- O₂
- SO₂
- PH₃
- NH₃
- NO₂
- HCN
- Cl₂
- ClO₂
- O₃

General Specifications

Size	5.7 x 2.9 x 1.5 in. / 14.5 x 7.4 x 3.8 cm
Weight	13.1 oz. / 370 g
Temperature	-4 to +122°F / -20 to +50°C -14 to +104°F / -10 to +40°C (PID)
Certifications and approvals	Class I, Div. 1, Gr. A, B, C, D American Bureau of Shipping - Toxic & PID only ATEX: CE Ex II 1 G Ex ia IIC T4* CE Ex II 2 G - IR model only Ex d ia IIC T4* IECEX: Ex ia IIC T4* Ex d ia IIC T4* - IR model only INMETRO: BR-Ex ia IIC T4* BR-Ex d ia IIC T4* - IR model only CE: European Conformity <small>*Temperature codes may vary as a function of the batteries installed. Please see owner's manual for a complete listing of compatible batteries and codes.</small>
Warranty	Full 2 year warranty including sensors (1 year Cl ₂ , NH ₃ , O ₃ , ETO, ClO ₂ & PID sensor)



GasAlertMicro 5 Detector

Order Number

%LEL, O ₂ , H ₂ S, CO, SO ₂ - alkaline batteries	M5-XWSY-A-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, SO ₂ - lithium polymer battery	M5-XWSY-R-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, SO ₂ - lithium polymer battery and pump	M5-XWSY-R-P-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, SO ₂ - lithium polymer battery and datalogging	M5-XWSY-R-D-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO, SO ₂ - lithium polymer battery, pump and datalogging	M5-XWSY-R-P-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO, NH ₃ - alkaline batteries	M5-XWAY-A-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, NH ₃ - lithium polymer battery	M5-XWAY-R-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, NH ₃ - lithium polymer battery and pump	M5-XWAY-R-P-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, NH ₃ - lithium polymer battery and datalogging	M5-XWAY-R-D-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO, NH ₃ - lithium polymer battery, pump and datalogging	M5-XWAY-R-P-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO, Cl ₂ - alkaline batteries	M5-XWCY-A-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, Cl ₂ - lithium polymer battery	M5-XWCY-R-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, Cl ₂ - lithium polymer battery and pump	M5-XWCY-R-P-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO, Cl ₂ - lithium polymer battery and datalogging	M5-XWCY-R-D-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO, Cl ₂ - lithium polymer battery, pump and datalogging	M5-XWCY-R-P-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO - alkaline batteries	M5-XW0Y-A-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO - alkaline batteries and pump	M5-XW0Y-A-P-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO - alkaline batteries, pump and datalogging	M5-XW0Y-A-P-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO - lithium polymer battery	M5-XW0Y-R-D-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO - lithium polymer battery and pump	M5-XW0Y-R-P-0-Y-N-00
%LEL, O ₂ , H ₂ S, CO - lithium polymer battery and datalogging	M5-XW0Y-R-D-D-Y-N-00
%LEL, O ₂ , H ₂ S, CO - lithium polymer battery, pump and datalogging	M5-XW0Y-R-P-D-Y-N-00

GasAlertMicro 5 Region Codes

For orders outside North America, change order number component “-N” to:

“-E”	Europe	“-B”	Brazil
“-U”	United Kingdom	“-X”	Other region with 3-pin UK plug
“-A”	Australia	“-Y”	Other region with 2-pin UK plug
“-C”	China/New Zealand		

Note: Listed above are **commonly ordered** instrument configurations. To create a custom GasAlertMicro 5 detector, use the configurator table on the next page or contact BW Technologies for a copy of the electronic pricing and order number configurator.

Gas Legend

%LEL	Combustible	ClO ₂	Chlorine dioxide
O ₂	Oxygen	NH ₃	Ammonia
H ₂ S	Hydrogen sulfide	PH ₃	Phosphine
CO	Carbon monoxide	HCN	Hydrogen cyanide
SO ₂	Sulfur dioxide	NO ₂	Nitrogen dioxide
Cl ₂	Chlorine	O ₃	Ozone



GasAlertMicro 5
Diffusion version with datalogging



GasAlertMicro 5
Pump version

GasAlertMicro5 Order Number and Pricing Configurator

Sensor - Toxic 2			
None (dummy sensor)	0		
CO and H ₂ S (TwinTox dual channel)	Y		
H ₂ S (hydrogen sulfide)	H		
CO (carbon monoxide)	M		
SO ₂ (sulfur dioxide)	S		
Cl ₂ (chlorine)	C		
ClO ₂ (chlorine dioxide)	V		
NH ₃ (ammonia)	A		
PH ₃ (phosphine)	P		
HCN (hydrogen cyanide)	Z		
NO ₂ (nitrogen dioxide)	D		
O ₃ (ozone)	G		
Sensor - Toxic 1			
None (dummy sensor)	0		
H ₂ S (hydrogen sulfide)	H		
CO (carbon monoxide)	M		
SO ₂ (sulfur dioxide)	S		
Cl ₂ (chlorine)	C		
ClO ₂ (chlorine dioxide)	V		
NH ₃ (ammonia)	A		
PH ₃ (phosphine)	P		
HCN (hydrogen cyanide)	Z		
NO ₂ (nitrogen dioxide)	D		
O ₃ (ozone)	G		
Sensor - Combustible Gases			
None (dummy sensor)	0		
%LEL (combustibles)	W		
None	0		
O ₂ (oxygen)	X		
Base Unit			
Base unit	\$380.00	M5	

A	Alkaline
R	Rechargeable lithium polymer battery pack and cradle charger
V	Rechargeable lithium polymer battery pack, cradle charger and vehicle adaptor
Sampling	
D	Diffusion
P	Motorized sampling pump
Datalogging	
0	None
D	Datalogging monitor (incl. Fleet Manager II software)
Housing	
Y	Yellow housing
B	Black housing
Region	
N	North America
E	Europe
C	China/New Zealand
U	United Kingdom
A	Australia
B	Brazil
X	Other region with 3-pin UK plug
Y	Other region with 2-pin EU plug

Order number: M5- - - - - - - - - - 00

For example, the order number for a GasAlertMicro 5 configured for O₂, %LEL, Cl₂, H₂S and CO and equipped with a rechargeable lithium polymer battery pack and cradle charger, motorized sampling pump, datalogging, yellow housing and North American power connectivity would be M5-XWCY-R-P-D-Y-N-00.

GasAlertMicro 5 PID Detector

Order Number

VOCs, %LEL, O ₂ , H ₂ S, CO - alkaline batteries	M5PID-XWQY-A-D-0-Y-N-00
VOCs, %LEL, O ₂ , H ₂ S, CO - alkaline batteries and pump	M5PID-XWQY-A-P-0-Y-N-00
VOCs, %LEL, O ₂ , H ₂ S, CO - alkaline batteries, pump and datalogging	M5PID-XWQY-A-P-D-Y-N-00
VOCs, %LEL, O ₂ , H ₂ S, CO - lithium polymer battery	M5PID-XWQY-R-D-0-Y-N-00
VOCs, %LEL, O ₂ , H ₂ S, CO - lithium polymer battery and pump	M5PID-XWQY-R-P-0-Y-N-00
VOCs, %LEL, O ₂ , H ₂ S, CO - lithium polymer battery, pump and datalogging	M5PID-XWQY-R-P-D-Y-N-00
VOCs, %LEL, O ₂ - alkaline batteries	M5PID-XWQ0-A-D-0-Y-N-00
VOCs, %LEL, O ₂ - alkaline batteries and pump	M5PID-XWQ0-A-P-0-Y-N-00
VOCs, %LEL, O ₂ - alkaline batteries, pump and datalogging	M5PID-XWQ0-A-P-D-Y-N-00
VOCs, %LEL, O ₂ - lithium polymer battery	M5PID-XWQ0-R-D-0-Y-N-00
VOCs, %LEL, O ₂ - lithium polymer battery and pump	M5PID-XWQ0-R-P-0-Y-N-00
VOCs, %LEL, O ₂ - lithium polymer battery, pump and datalogging	M5PID-XWQ0-R-P-D-Y-N-00
VOCs - alkaline batteries	M5PID-00Q0-A-D-0-Y-N-00
VOCs - alkaline batteries and pump	M5PID-00Q0-A-P-0-Y-N-00
VOCs - alkaline batteries, pump and datalogging	M5PID-00Q0-A-P-D-Y-N-00
VOCs - lithium polymer battery	M5PID-00Q0-R-D-0-Y-N-00
VOCs - lithium polymer battery and pump	M5PID-00Q0-R-P-0-Y-N-00
VOCs - lithium polymer battery, pump and datalogging	M5PID-00Q0-R-P-D-Y-N-00

GasAlertMicro 5 PID Region Codes

For orders outside North America, change order number component “-N” to:

“-E” Europe	“-B” Brazil
“-U” United Kingdom	“-X” Other region with 3-pin UK plug
“-A” Australia	“-Y” Other region with 2-pin UK plug
“-C” China/New Zealand	

Note: Listed above are commonly ordered instrument configurations. To create a custom GasAlertMicro 5 PID detector, use the configurator table on the next page or contact BW Technologies for a copy of the electronic pricing and order number configurator.

Gas Legend

VOCs	Volatile organic compounds	ClO ₂	Chlorine dioxide
%LEL	Combustible	NH ₃	Ammonia
O ₂	Oxygen	PH ₃	Phosphine
H ₂ S	Hydrogen sulfide	HCN	Hydrogen cyanide
CO	Carbon monoxide	NO ₂	Nitrogen dioxide
SO ₂	Sulfur dioxide	O ₃	Ozone
Cl ₂	Chlorine		



GasAlertMicro 5 PID
Diffusion version with datalogging

GasAlertMicro 5 PID
Pump version with datalogging

GasAlertMicro⁵PID Order Number and Pricing Configurator

Sensor - Toxic 2		Battery	
None (dummy sensor)	0	A	Alkaline
CO and H ₂ S (TwinTox dual channel)	Y	R	Rechargeable lithium polymer battery pack and cradle charger
H ₂ S (hydrogen sulfide)	H	V	Rechargeable lithium polymer battery pack, cradle charger and vehicle adaptor
CO (carbon monoxide)	M	Sampling	
SO ₂ (sulfur dioxide)	S	D	Diffusion
Cl ₂ (chlorine)	C	P	Motorized sampling pump
ClO ₂ (chlorine dioxide)	V	Datalogging	
NH ₃ (ammonia)	A	0	None
PH ₃ (phosphine)	P	D	Datalogging monitor (incl. Fleet Manager II software)
HCN (hydrogen cyanide)	Z	Housing	
NO ₂ (nitrogen dioxide)	D	Y	Yellow housing
O ₃ (ozone)	G	B	Black housing
Sensor - Toxic 1		Region	
None (dummy sensor)	0	N	North America
PID (photoionization detector) for VOCs (volatile organic compounds)	Q	E	Europe
Sensor - Combustible Gases		C	China/New Zealand
None (dummy sensor)	0	U	United Kingdom
%LEL (combustibles)	W	A	Australia
Sensor - Oxygen		B	Brazil
None	0	X	Other region with 3-pin UK plug
O ₂ (oxygen)	X	Y	Other region with 2-pin EU plug
Base Unit			
Base unit	M5PID		

Order number:

M5PID										00
-------	--	--	--	--	--	--	--	--	--	----

For example, the order number for a GasAlertMicro 5 PID configured for O₂, %LEL, VOCs, H₂S and CO and equipped with a rechargeable lithium polymer battery pack and cradle charger, motorized sampling pump, datalogging, yellow housing and North American power connectivity would be M5PID-XWQY-R-P-D-Y-N-00.

GasAlertMicro 5 IR Detector

Order Number

CO ₂ (IR), %LEL, O ₂ , H ₂ S, CO - alkaline batteries	M5IR-XWBY-A-D-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S, CO - lithium polymer battery	M5IR-XWBY-R-D-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S, CO - lithium polymer battery and pump	M5IR-XWBY-R-P-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S, CO - lithium polymer battery and datalogging	M5IR-XWBY-R-D-D-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S, CO - lithium polymer battery, pump and datalogging	M5IR-XWBY-R-P-D-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S - alkaline batteries	M5IR-XWBH-A-D-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S - lithium polymer battery	M5IR-XWBH-R-D-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S - lithium polymer battery and pump	M5IR-XWBH-R-P-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S - lithium polymer battery and datalogging	M5IR-XWBH-R-D-D-Y-N-00
CO ₂ (IR), %LEL, O ₂ , H ₂ S - lithium polymer battery, pump and datalogging	M5IR-XWBH-R-P-D-Y-N-00
CO ₂ (IR), %LEL, O ₂ - alkaline batteries	M5IR-XWB0-A-D-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ - lithium polymer battery	M5IR-XWB0-R-D-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ - lithium polymer battery and pump	M5IR-XWB0-R-P-0-Y-N-00
CO ₂ (IR), %LEL, O ₂ - lithium polymer battery and datalogging	M5IR-XWB0-R-D-D-Y-N-00
CO ₂ (IR), %LEL, O ₂ - lithium polymer battery, pump and datalogging	M5IR-XWB0-R-P-D-Y-N-00
CO ₂ (IR) - alkaline batteries	M5IR-00B0-A-D-0-Y-N-00
CO ₂ (IR) - lithium polymer battery	M5IR-00B0-R-D-0-Y-N-00
CO ₂ (IR) - lithium polymer battery and pump	M5IR-00B0-R-P-0-Y-N-00
CO ₂ (IR) - lithium polymer battery and datalogging	M5IR-00B0-R-D-D-Y-N-00
CO ₂ (IR) - lithium polymer battery, pump and datalogging	M5IR-00B0-R-P-D-Y-N-00

GasAlertMicro 5 IR Region Codes

For orders outside North America, change order number component “-N” to:

“-E” Europe	“-B” Brazil
“-U” United Kingdom	“-X” Other region with 3-pin UK plug
“-A” Australia	“-Y” Other region with 2-pin UK plug
“-C” China/New Zealand	

Note: Listed above are **commonly ordered** instrument configurations. To create a custom GasAlertMicro 5 IR detector, use the configurator table on the next page or contact BW Technologies for a copy of the electronic pricing and order number configurator.

Gas Legend

CO ₂ Carbon dioxide	CO Carbon monoxide
%LEL Combustible	SO ₂ Sulfur dioxide
O ₂ Oxygen	NH ₃ Ammonia
H ₂ S Hydrogen sulfide	O ₃ Ozone



GasAlertMicro 5 IR
Diffusion version with datalogging

GasAlertMicro 5 IR
Pump version with datalogging

GasAlertMicro⁵IR Order Number and Pricing Configurator

Sensor - Toxic 2		Battery	
None (dummy densor)	0	A	Alkaline
CO and H ₂ S (TwinTox dual channel)	Y	R	Rechargeable lithium polymer battery pack and cradle charger
H ₂ S (hydrogen sulfide)	H	V	Rechargeable lithium polymer battery pack, cradle charger and vehicle adaptor
CO (carbon monoxide)	M	Sampling	
SO ₂ (sulfur dioxide)	S	D	Diffusion
NH ₃ (ammonia)	A	P	Motorized sampling pump
O ₃ (ozone)	G	Datalogging	
Sensor - Toxic 1		0	None
None (dummy sensor)	0	D	Datalogging monitor (incl. Fleet Manager II software)
IR (infrared) for CO ₂ (carbon dioxide)	B	Housing	
Sensor - Combustible Gases		Y	Yellow housing
None (dummy sensor)	0	B	Black housing
%LEL (combustibles)	W	Region	
Sensor - Oxygen		N	North America
None	0	E	Europe
O ₂ (oxygen)	X	C	China/New Zealand
Base Unit		U	United Kingdom
Base unit	M5IR	A	Australia
		B	Brazil
		X	Other region with 3-pin UK plug
		Y	Other region with 2-pin EU plug

Order number:

M5IR										00
------	--	--	--	--	--	--	--	--	--	----

For example, the order number for a GasAlertMicro 5 IR configured for O₂, %LEL, CO₂, H₂S and CO and equipped with a rechargeable lithium polymer battery pack and cradle charger, motorized sampling pump, datalogging, yellow housing and North American power connectivity would be M5IR-XWBY-R-P-D-Y-N-00.

GasAlertMicro 5 Series

5 - GAS DETECTOR

Confined Space Kit

	Order Number
GasAlertMicro 5 Series deluxe confined space kit <i>Detector and calibration gas sold separately</i>	M5-CK-DL
Carrying case for GasAlertMicro 5 Series with foam and lid insert	M5-CK-CC

Carrying Accessories

	Order Number
Concussion-proof boot, diffusion units	GA-BM5-1
Concussion-proof boot, pump units	GA-BM5-2
Carrying holster	GA-HM5
Alligator-style clip (stainless steel)	GA-AG-2
Neck strap with safety release	GA-NS-1
Short strap (6 in./15.2 cm)	GA-LY-1
Extension strap (4 ft./1.2 m)	GA-ES-1
Armband	GA-ARM-1
Chest harness	GA-CH-2

Datalogging Accessories and Options

	Order Number
MultiMedia card	M5-MMC
USB memory card reader	CR-MMC-USB1



Concussion-Proof Boot
GA-BM5-2
*For GasAlertMicro 5 Series
pumped units*



Concussion-Proof Boot
GA-BM5-1
*For GasAlertMicro 5 Series
diffusion units*

Deluxe Confined Space Kit
M5-CK-DL
*Order detector and calibration
gas separately*



Carrying Holster
GA-HM5
Fits securely on belt

Power Accessories, Options and Spares

Order Number

Alkaline battery pack, yellow*	M5-BAT0501
Alkaline battery pack, black*	M5-BAT0501B
Alkaline battery pack, European-style safety screws, yellow*	M5-BAT0502
Alkaline battery pack, European-style safety screws, black*	M5-BAT0502B
Lithium polymer rechargeable battery pack, yellow*	M5-BAT08
Lithium polymer rechargeable battery pack, black*	M5-BAT08B
Cradle charger and rechargeable battery pack, yellow*	M5-C01-BAT08
Cradle charger and rechargeable battery pack, black*	M5-C01-BAT08B
Cradle charger for rechargeable battery packs	M5-C01
Battery latch, replacement	M5-BL-1
12 Vdc vehicle adaptor cable for use with cradle charger (M5-C01)	GA-V-CHRG4

*Battery packs should be used with the new versions GasAlertMicro 5 Series gas detectors that have red circuit boards. See the Sensor Accessories, Spares and Replacements section for order information on batteries for the old version GasAlertMicro 5 Series gas detectors (green circuit boards).



Alkaline Battery Pack
M5-BAT0501/M5-BAT0501B
M5-BAT0502/M5-BAT0502B



Rechargeable Battery Pack
M5-BAT08/M5-BAT08B



Replacement Battery Latch
M5-BL-1



Vehicle Adaptor 12 Vdc
GA-V-CHRG4
Vehicle adaptor cable for use with cradle charger (M5-C01)



Cradle Charger Kit with Battery
M5-C01-BAT08 / M5-C01-BAT08B
Complete with charger and rechargeable battery pack



Cradle Charger
M5-C01
Cradle charger for rechargeable battery packs

GasAlertMicro 5 Series

Sampling/Testing Equipment and Spares

	Order Number
Test cap and hose (1.5 ft./0.5 m) replacement	M5-TC-1
Integral motorized pump kit - Yellow - Black	M5-PUMP M5-PUMPB
<i>Includes motorized pump cover, 1 ft./30 cm sample probe with hydrophobic barrier (water trap) and particulate filters, 5 ft./1.5 m sampling tubing, three spare particulate filters and one spare water trap filter.</i>	
Auxiliary pump filter compatible with hose	M5-QCONN-K1
Auxiliary pump filter - Kit of 5 - Kit of 100	M5-AF-K2 M5-AF-K2-100
MicroDock II automatic test and calibration system:	
- Base station and GasAlertMicro 5 Series docking module (charging) with charging cable	DOCK2-2-1C1K-00-N*
- Base station and GasAlertMicro 5 Series docking module (non-charging)	DOCK2-2-1J-00-N*
- GasAlertMicro 5 Series docking module (charging), no charging cable	DOCK2-0-1K-00-N
- GasAlertMicro 5 Series docking module (non-charging)	DOCK2-0-1J-00-N
<i>For complete MicroDock II system configuration information, see MicroDock II section.</i>	
Manual aspirator pump kit with probe (1 ft./0.3 m)	GA-AS02

For a complete list of sampling probes, hoses, accessories and spares, see Sampling Accessories section.

**Change order number suffix "-N" to: "-E" for European versions, "-U" for United Kingdom versions, "-A" for Australian versions.*



Replacement Test Cap and Hose
M5-TC-1



Auxiliary Pump Filter with Hose Connector
M5-QCONN-K1



M5 Pump
M5-PUMP



Auxiliary Pump Filter
M5-AF-K2 / M5-AF-K2-100
Easily attaches with a quick connect fitting to provide additional pump protection



Replacement Diffusion Cover
M5-DC-1




Manual Aspirator Pump
GA-AS02
For remote sampling. Complete with probe, hose and aspirator pump

Sensor Spares and Replacements	Order Number
Quad sensor screen filters, kit of 2	M5-SS
Alkaline battery pack (for use with GasAlertMicro 5 Series detectors with green circuit boards)	M5-BAT02
Alkaline battery pack (for use with GasAlertMicro 5 Series detectors with green circuit boards), European-style safety screws	M5-BAT03
Rechargeable lithium polymer battery pack (for use with GasAlertMicro 5 Series detectors with green circuit boards), yellow or black	M5-BAT07 M5-BAT07B
Replacement power supply for chargers	POWER-UPS-1
Replacement pump, yellow	M5-PR-1
Replacement pump, black	M5-PRB-1
Replacement diffusion cover, yellow	M5-DC-1
Replacement diffusion cover, black	M5-DCB-1
Replacement carbon dioxide (CO ₂) IR sensor	SR-B04
Replacement volatile organic compounds (VOC) PID sensor, 10.6eV	SR-Q07
Replacement electrode stacks for PID sensor (SR-Q07), kit of 2	M5PID-ES-1
Replacement PID lamp, (10.6eV) for PID sensor (SR-Q07)	RL-PID10.6
Cleaning kit for PID sensor	M5PID-CLN-K1
Replacement TwinTox sensor - carbon monoxide (CO) and hydrogen sulfide (H ₂ S)	D4-RHM04
Replacement hydrogen sulfide (H ₂ S) sensor	PS-RH04S
Replacement carbon monoxide (CO) sensor	PS-RM04
Replacement carbon monoxide (CO) sensor, H ₂ resistant	PS-RM04H
Replacement sulfur dioxide (SO ₂) sensor	PS-RS04
Replacement chlorine (Cl ₂) sensor	PS-RC10
Replacement hydrogen cyanide (HCN) sensor	PS-RZ10
Replacement nitrogen dioxide (NO ₂) sensor	PS-RD04
Replacement ammonia (NH ₃) sensor	SR-A04
Replacement phosphine (PH ₃) sensor	SR-P04
Replacement ozone (O ₃) sensor	SR-G04
Replacement chlorine dioxide (ClO ₂) sensor	SR-V04
Replacement combustible sensor with heavy duty silicone filter*	SR-W04
Replacement combustible sensor without heavy duty silicone filter*	SR-W04-UF
<i>* Advisory: Detectors are equipped on a standard basis with SR-W04 combustible sensors. This sensor includes a heavy duty silicone filter that make it ideal for use in environments that have known sources of silicone or vapors containing silicon. The SR-W04 silicone filter equipped sensor should not be used when monitoring diesel, kerosene, jet fuel or other heavy hydrocarbon vapors with flashpoint temperatures above 38°C (100°F).</i>	
Replacement oxygen (O ₂) sensor	SR-X10
Dummy sensor for 3-pin O ₂ or 3-pin TwinTox locations	SR-DUMM1
Dummy sensor for LEL location	SR-DUMM2
Dummy sensor for PID location	SR-DUMM3

PID Cleaning Kit

M5PID-CLN-K1
For PID Sensors



Replacement 10.6 eV PID Lamp

RL-PID10.6
For PID Sensors



Replacement Electrode Stack

M5PID-ES-1
For PID Sensors



Replacement PID Sensor

SR-Q07



Replacement IR Sensor

SR-B04





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.