

Data Sheet

Mixing / Magnetic Stirrers



Midi MR 1 digital IKAMAG®

Powerful magnetic stirrer without heating.

- Flat, sturdy stainless steel casing
- Non-locking motor
- Infinitely variable speed
- Digital LED speed display
- Timer (0 - 56 min) or continuous operation
- For stirring quantities up to 50 liters (H₂O)

Accessories: TRIKA® 40 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 40 Magnetic stirring bar, H 11 Mains cable UK plug, TRIKA® 25 Magnetic stirring bar, H 11 Mains cable CH plug, IKAFLON® 80 Magnetic stirring bar, IKAFLON® 50 Magnetic stirring bar, H 11 Mains cable Euro plug, H 11 Mains cable USA plug, RSE Stirring bar remover

Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	50
Motor rating input [W]	70
Motor rating output [W]	19
Speed display	LCD
Speed range [rpm]	0 - 1000
Stirring bar length max. [mm]	80
Set-up plate material	stainless steel 1.4301
Set-up plate dimensions [mm]	350 x 350
Dimensions (W x H x D) [mm]	360 x 110 x 430
Weight [kg]	10.7
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	230 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	70
Ident. No.	2621900



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.