

Data Sheet

Mixing / Magnetic Stirrers



Mini MR standard IKAMAG®

The improvement of the magnetic stirrer. new: For stirring quantities up to 1.000 ml (H₂O)
new: Infinitely variable speed from 0 - 2.500 rpm
- White set-up plate suitable for observing color reactions

Accessories: IKAFLON® 15 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover, IKAFLON® 20 Magnetic stirring bar

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	1
Stirring quantity max. (H ₂ O) [l]	1
Motor rating input [W]	3
Motor rating output [W]	2
Speed display	none
Speed range [rpm]	0 - 2500
Stirring bar length max. [mm]	30
Set-up plate material	polyester
Set-up plate dimensions [mm]	115 x 115
Dimensions (W x H x D) [mm]	114 x 37 x 127
Weight [kg]	0.25
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	no
Analog output	no
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	3
DC Voltage [V=]	12
Current consumption [mA]	300
Ident. No.	3674000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.