

Data Sheet

Mixing / Magnetic Stirrers



RH basic 2 IKAMAG®

RH basic 2

Economic magnetic stirrer with stainless steel heating plate.

- Fixed safety circuit 400 °C
- Soft-start stirring motor

Accessories: IKAFLON® 15 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, H 38 Holding rod, TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover, IKAFLON® 20 Magnetic stirring bar

Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	10
Stirring quantity max. (H ₂ O) [l]	10
Motor rating input [W]	15
Motor rating output [W]	2
Speed range [rpm]	100 - 2000
Heat output [W]	400
Heating temperature range [°C]	room temp. - 320
Heat control	scale 1 - 6
Speed control	scale 0 - 6
Fixed safety circuit [°C]	400
Set-up plate material	stainless steel 1.4301
Set-up plate dimensions [mm]	Ø 125
Dimensions (W x H x D) [mm]	168 x 105 x 220
Weight [kg]	2.4
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	220 - 240 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	415
Ident. No.	3339000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.