



Tube Mill control

The world's first patented Tube Mill control is a batch mill with disposable grinding chamber. Eliminates possibility of cross-contamination and the effort of cleaning. The grinding chamber and cover are made of a transparent material so grinding tests can be observed at any time. The mill can be used for hard (Mohs hardness up to 5), dry and brittle materials. It is especially suitable for grinding seeds, such as corn and wheat. During development of the mill, particular emphasis was placed on security. The mill will only start when the hood is closed. When the grinding chamber is not inserted properly or not closed properly, the drive unit will display an error message and the drive will not start. During operation, the grinding chamber cannot be opened. The drive and the grinding chambers are secured with a labyrinth seal. No dust can escape from the chamber or penetrate the drive.

- Clearly arranged, multilingual OLED-display
- Timer, adjustable from 5 s to 3 min
- USB interface for control and documentation of all the parameters
- Interval operation available
- Infinitely variable speed from 5000 to 25000 rpm
- Various operating modes
- Adjustable safety speed
- Adjustable safety time
- Programmable and storable test conditions
- Error Code Display
- Reproducible test results
- Easy operation with touch keypad
- Dust proof sealed housing

Technical Data

Process type	batch
Operating principle	cutting/impact
Motor rating input [W]	100
Motor rating output [W]	80
Speed range [rpm]	5000 - 25000
Circumferential speed max. [m/s]	65
Usable volume max. [ml]	40
Feed hardness max. [Mohs]	5
Feed grain size max. [mm]	10
Material beater/cutter	stainless steel 1.4034
Power-on time ON [min]	3
Milling chamber, can be cooled with water	no
Mill feed can be cooled in milling chamber with dry ice	yes
Mill feed can be cooled in milling chamber with liquid nitrogen	no
Dimensions (W x H x D) [mm]	180 x 170 x 300
Weight [kg]	2.7
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 30
USB interface	yes
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	100

Ident. No. 0004180000

- Quiet operation

Accessories: MT 40



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.