



FLD-8/8 ~ 8 litre digital duobath

For consistent controlled cooking, Clifton Water baths allows chefs to cook in a precise temperature controlled environment, to produce consistently perfect results. Ideal for sous vide and other low temperature cooking, these baths are an indispensable piece of equipment for all leading chefs worldwide. The duobath range allows chefs to use each chamber simultaneously at two different temperatures.

Versatility~

As with all Clifton duobaths, each side can be operated at two different temperatures simultaneously and with two different liquids e.g. water in one side and oil in the other.

Precise temperatures~

Using the same high precision controllers found on all other Clifton Food Range products, accuracy and repeatability are guaranteed. Actual temperature is clearly displayed to 0.1°C.

If required, the integrated timer on each controller can be set between 1 minute and 99 hours. There is audio/visual notification at the end of the set period after which the bath still continues to operate at the set temperature.

Current time and temperature settings are retained in memory even after 'power off.'

High quality build and features~

Temperatures can be easily and rapidly set with the push button, wipe clean control panel. The entire case is constructed from high quality stainless steel.

If the water drops below the recommended minimum level or the unit is inadvertently switched on without being filled with water, '**FILL**' appears on the display as a visual alert and gives run dry protection.

Side lifting handles make it easy to carry the bath around the kitchen and the product is supplied with two lids which have easy grab insulated handles. The bath is also supplied with two removable stainless steel perforated shelves which provide effective distribution of heat uniformly throughout the chamber by convection. Drain tap on each chamber.

In common with all Clifton Baths, the product is powered from a standard 13 amp wall socket.



Temperature:

Display/resolution: Digital LED/ 0.1°C
Temp. range: Ambient + 5°C ~ 95°C
Temp. setting: Pushbutton
Stability/uniformity: $\pm 0.2^{\circ}\text{C}$ / $\pm 0.1^{\circ}$

Timer:

Display/resolution: Digital LED / 1 minute increments
Duration: 1 minute – 99 hours
Cycle end: Audio/visual alert

General:

Dimensions (mm) : overall ~ 600w x 332d x 290h
: working ~ 240w x 300d x 150h (each chamber)
Electrical supply: 230v
Power consumption: 1.6kW
Safety: Visual 'FILL' message on low water level
Run-dry protection

Supplied complete with drain taps, lids and removable shelves

Product shown with accessory P270 divider



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.