

Interchange IM914 Carrier System

Technical Datasheet

Description

IM914 Interchange 900 face shield carrier system with spring attachment and ratchet angle adjustment.

Applications

The IM914 carrier system is suitable for general use in industry for protection of the eyes and face when used with the Protector Tuffmaster I or similar styles of helmet. The IM914 can also be used in high temperature or chemical environments. The IM914 has been designed to meet the requirements of EN166 for impact, liquid splash and molten metal splash. The exact approval specification is dependent on the face shield material specified.



Approval Information

IM914 Carrier System	EN166 B 39; EN1731 SG
----------------------	-----------------------

Materials

Frame:	Powder Coated Aluminium
Seals:	Flame retardant closed cell foam and rubber compound

Maintenance and Cleaning

Carrier system should be inspected for deterioration or damage before each use. If the carrier system is damaged it should be discarded. Clean regularly using warm water and a mild detergent, pat or air dry.

Disposal

As the carrier system and its components are subject to dirt, dust and liquids etc., they cannot be recycled. Disassemble and dispose of as solid waste.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.