Water Baths

with BioCote® antimicrobial protection

Water Baths are one of the most common pieces of laboratory equipment used today, the Stuart® range offers three sizes 6, 15 and 24L with digital control.

Stuart® Water Baths

- Choice of sizes - 6, 15 or 24 Litres
- Digital display and selection of temperature
- Low level water sensor
- Integral drain
- Supplied with robust polycarbonate lid

Three robust and reliable water baths, each with easy to clean stainless steel tank and sturdy metal outer casing. Digital water baths with easy to use temperature control and clear to read LED water temperature. Incorporated over temperature protection system that tracks the set temperature and controls the heater in the event of a fault. The heater is mounted underneath the tank to allow easy cleaning. Includes low level water sensor which cuts power to prevent the bath boiling dry. Incorporated drain for easy emptying of the bath.

Bath covers are included as standard with each bath to help reduce heat losses and evaporation. The covers are manufactured from robust polycarbonate allowing full visibility of the bath contents.

Technical Specification

	SW6D	SW15D	SW24D
Capacity	6L	15L	24L
Temperature range	Ambient +5°C to 99.9°C	Ambient +5°C to 99.9°C	Ambient +5°C to 99.9°C
Temperature stability	+/- 0.5C	+/- 0.5C	+/- 0.5C
Internal dimensions (w x d x h),mm	300 x x150 x 200	300 x 325 x 200	300 x 500 x 200
Overall dimensions (w x d x h), mm	335 x 230 x 280	335 x 408 x 280	335 x 584 x 280
Net Weight, kg	6.5kg	9.0kg	12.8kg
Heater Power	500W	1000W	1700W
Electrical supply	230V, 50Hz, 500W	230V, 50Hz, 1000W	230V, 50Hz, 1700W
Electrical supply	230V, 50Hz	230V,50Hz	230V, 50Hz
IP Rating	31	31	31

Ordering Information

Model	Description
SWB6D	Digital water bath 6L
SWB15D	Digital water bath 15L
SWB24D	Digital water bath 24L

Model	Description
SWB6D/1	Polycarbonate lid for 6L bath
SWB15D/1	Polycarbonate lid for 15L bath
SWB24D/1	Polycarbonate lid for 24L bath

Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.

UK Office
Keison Products,
P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.
Tel: +44 (0)330 088 0560
Fax: +44 (0)1245 808399
Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.