

Techne® Analogue Dri-Blocks®

DB-2A

- Small, light and compact footprint, economical price
- Can hold up to 2 aluminium insert blocks or one 96-well plate block
- Temperature setting is by a calibrated dial
- Temperature range from ambient to 100°C
- Fast heat-up rate: 30°C to 100°C in just 12 minutes
- Temperature stability at 40°C: $\pm 0.05^\circ\text{C}$

DB-3A

- Temperature range from ambient to 200°C for higher temperature applications
- Can hold up to 3 aluminium insert blocks or one 96-well plate block
- Analogue: temperature setting is by a calibrated dial
- Powerful heater for fast heat-up rate: 30°C to 200°C in just 30 minutes
- Temperature stability at 40°C: $\pm 0.1^\circ\text{C}$

DB-3

- The DB-3 is designed to hold up to 3 aluminium insert blocks or one 96-well plate block
- Temperature setting is by a calibrated dial
- Temperature range from ambient to 100°C
- Fast heat-up rate: 30°C to 100°C in just 18 minutes
- Temperature stability at 40°C: $\pm 0.05^\circ\text{C}$



Specifications

Parameter	DB-2A	DB-3	DB-3A
Temperature range	Ambient +5°C to 100°C	Ambient +5°C to 100°C	Ambient +5°C to 200°C
Number of insert blocks	2	3	3
Temperature stability @ 40°C	$\pm 0.05^\circ\text{C}$	$\pm 0.05^\circ\text{C}$	$\pm 0.1^\circ\text{C}$
Temperature stability @ 100°C	$\pm 0.1^\circ\text{C}$	$\pm 0.1^\circ\text{C}$	$\pm 0.15^\circ\text{C}$
Temperature setting	Rotary dial	Rotary dial	Rotary dial
Temperature scale graduation	2°C	2°C	2°C
Temperature display	n/a	n/a	n/a
Maximum variation between identical blocks @ 40°C	0.2°C	0.2°C	0.2°C
Set point accuracy	$\pm 2^\circ\text{C}$	$\pm 2^\circ\text{C}$	$\pm 2^\circ\text{C}$
Heat up time: 30 to 37°C	8	8	8
Heat up time: 30 to 56°C	9	12	12
Heat up time: 30 to Maximum	12	18	30
Heater power	300W	450W	450W
Power supply	230V or 115V 50-60 Hz	230V or 115V 50-60Hz	230V or 115V 50-60Hz
Dimensions (W x D x H), mm	202 x 260 x 105	279 x 260 x 105	279 x 260 x 105
Shipping Weight	4kg	6kg	6kg

Ordering Information

Part number	Model number	Description
FDB02AD	DB-2A	Techne® analogue Dri-Block® heater. Ambient + 5°C to 100°C, 2 blocks (230V)
FDB02AP	DB-2A	Techne® analogue Dri-Block® heater. Ambient + 5°C to 100°C, 2 blocks (115V)
FDB03OD	DB-3	Techne® analogue Dri-Block® heater. Ambient + 5°C to 100°C, 3 blocks (230V)
FDB03OP	DB-3	Techne® analogue Dri-Block® heater. Ambient + 5°C to 100°C, 3 blocks (115V)
FDB03AD	DB-3A	Techne® analogue Dri-Block® heater. Ambient + 5°C to 200°C, 3 blocks (230V)
FDB03AP	DB-3A	Techne® analogue Dri-Block® heater. Ambient + 5°C to 200°C, 3 blocks (115V)



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.