



3M™ Detcon™ Model FP-524D

Combustible Gas Sensor

Description

Detcon Model FP-524D is a “Smart” gas detection sensor designed to detect and monitor combustible gas in air over the range of 0-100% LEL (lower explosive limit) using matched-pair catalytic bead technology.

Model FP-524D features Detcon’s MicroSafe™ intelligent electronics, non-intrusive operator interface and comprehensive fault diagnostics. The sensor transmitter features an advanced universal design that fits all existing Detcon matched-pair catalytic bead sensors dating back more than 20 years. The sensor assembly includes the detector in stainless steel housing, a base connector board, an explosion proof enclosure (available in aluminum or stainless steel), a plug-in control transmitter circuit, and a splashguard with integral cal port. The packaging is Explosion Proof (Class I, Division 1, Groups C and D).

Model FP-524D is equipped with a standard analog 4-20 mA current signal equivalent to the sensor range of detection, one-man remote calibration, self-adjusting zero and span, and LED indicators for fault and calibration status. A HART communications option is also available. Detcon’s combustible gas sensor has an infinite shelf life and is supported by a 2-year warranty.

Features

- Certified to ISA performance standards
- cCSAus approved for for Class I, Division 1, Groups C & D
- Transmitter design fits all existing Detcon Catalytic Bead Sensors dating back 20 years
- Simple menu driven calibration - less than 3 minutes
- LED display and LED indicators for FAULT and CAL status
- Plug-in field-replaceable transmitter
- Long sensor life: average +5 years in harsh offshore drilling/production environments
- High resistance to poisons such as sulfides, chlorides, silicon-based contaminants etc.
- Low power consumption (less than 3.5 watts versus 8+ watts on competitive brands)
- Extensive Fault diagnostics

Applications

- Oil and Gas Drilling Rigs
- Oil and Gas Production Sites
- Offshore Production Platforms
- FPSOs
- LNG/CNG Plants
- Refining and Petrochemical
- Pulp and Paper Mills
- Waste Water Treatment Plants



3M™ Detcon™ Model FP-524D

Combustible Gas Sensor

System Specifications

Sensor Type

Matched-pair catalytic bead

Sensor Life

3 to 5 years typical

Measurement Range

0-100% LEL (lower explosive limit)

Accuracy/Repeatability

±3% 0-50% LEL

±5% 50-100% LEL

Response/Clearing Time

T50 <10 seconds; T90 <30 seconds

Zero Drift

<5% per year

Outputs

Linear 4-20 mA DC

HART (optional)

Electrical Classification

Explosion proof

CSAus

Class I, Division 1, Groups C, D (Tamb = -25°C to +40°C)

Class I, Zone 1, Group IIB

cCSA

Class I, Division 1, Groups C, D (Tamb = -40°C to +40°C)

Class I, Zone 1, Group IIB

Performance Approvals

CSA C22.2 #152-M1984, ISA 12.13.01-2003

Safety Approvals

cCSAus

Ingress Protection

NEMA 4X, IP66

Warranty

Sensor: 2 year warranty

Transmitter: 2 year warranty

Environmental Specifications

Operating Temperature Range

-40°C to +40°C; -40°F to 104°F (CANADA)

-25°C to +40°C; -13°F to 104°F (USA)

Storage Temperature Range

-40°C to +75°C; -40°F to +167°F

Operating Humidity Range

5-100% RH non-condensing

Operating Pressure Range

Atmospheric ±10%

Mechanical Specifications

Dimensions

10”H (including splashguard) x 6.1”W x 4.3”D

254mmH x 155mmW x 109mmD

Mounting holes (J-box) 5.5”; 140mm center to center

Weight

6 lbs; 2.72kg (w/aluminum j-box)

9 lbs; 4.08kg (w/stainless steel j-box)

Electrical Specifications

Power Input

12-28 VDC

Power Consumption

Normal operation = 68mA (<1.7 watt)

Maximum = 87mA (2 watts)

RFI/EMI Protection

Complies with ISO 92.0.01

Analog Output

Linear 4-20mA DC (1,000 ohms max loop load @ 24VDC)

0mA All Fault Diagnostics

2mA In-Calibration

4-20mA 0-100% full-scale

22mA Over-range condition

Status Indicators

4-digital LED display with gas concentration

Full-script menu prompts for AutoSpan,

Set-up Options, and Fault Reporting

4 LEDs for Alarm 1, Alarm 2, Fault, and Calibration

Faults Monitored

Loop, Input Voltage, Zero

Sensor, Processor, Memory, Calibration

Cable Requirements

Power/Analog

3-wire shielded cable

Maximum distance is 13,300 feet with 14 AWG

I/O Protection

Over-voltage, Miswiring, EMI/RFI Immunity

Specifications subject to change without notice

Order Guide

PN 965-525420-100 Model FP-524D in Aluminum Junction Box

PN 965-52542B-100 Model FP-524D-316SS in Stainless Steel Junction Box

PN 9H5-525420-100 Model FP-524D with HART in Aluminum Junction Box

PN 9H5-52542B-100 Model FP-524D-316SS with HART in Stainless Steel Junction Box



Copyright © 2018 3M, 3M Gas & Flame Detection.
All rights reserved.
gasdetection.3m.com. GF-30116B

Americas Texas (USA)

4055 Technology Forest
Blvd. The Woodlands,
TX 77381
Tel.: +1-800-247-7257
Fax: +1-281-292-2860

EMEA

ZI Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX, France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

Asia Pacific

290 Guiqiao Road
Pudong, Shanghai 201206
People's Republic of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365