

Dräger Pac[®] 7000



ST-2507-2005

Small and robust, ergonomic and intuitive, economic and powerful – the Dräger Pac 7000 is tailor-made for personal monitoring at the workplace. This innovative single gas detector is equipped with a wide range of functions and is suitable for many different applications in day-to-day industrial settings. The detector is an impressive instrument, offering a high level of reliability and rapid warning against harmful concentrations of CO, CO₂, Cl₂, HCN, H₂S, NH₃, NO₂, O₂, PH₃, SO₂.



ST-1758-2005

Dräger Pac 7000:
High performance and unlimited use.

Small and robust

With its compact, handy, pocket-sized design, Dräger Pac 7000 is tailor-made for personal monitoring in daily work activities. Dräger Pac 7000 was specially designed as a small and robust instrument to meet work requirements. The impact-resistant housing features a protective rubber coating and is resistant to corrosive chemicals. Dräger Pac 7000 meets the requirements of IP 65. What is more, protection against electromagnetic effects was specially optimized, while a stable and tightly locking crocodile clip made of stainless steel allows the instrument to be fastened securely to the wearer's clothing. To allow for individual preferences, the crocodile clip can be turned and the two alarm lights are positioned diagonally opposite at the corners of the instrument. Easy battery and sensor replacement are key factors to ensure a long instrument life.

Concentration display

The concentration display uses no written text (to avoid language problems), showing all information in the form of large numerals or symbols. In case of an alarm, or at the push of a button, the display can be backlit for better readability. The currently measured concentration is displayed contin-

uously, as are notice and warning functions. In addition, the respective peak concentration, average concentration (TWA value) and short-term exposure limit (STEL) relating to the measurement period can be accessed.

New sensor technology "en miniature"

Dräger Pac 7000 boasts the latest in sensor technology. The small size of the sensor supports the application-oriented design of the instrument. Any gas hazards that may occur are displayed immediately thanks to the very short diffusion paths inside the instrument and the extremely quick electrochemical reaction times achieved by the new sensors. The sensor is positioned inside the housing such as to allow gas to reach it from above and from in front. This positioning minimizes the danger of the gas inlet opening being accidentally covered.

Alarm / warning functions

In conjunction with a vibration alarm, a visual and audible alarm is triggered if the two adjustable alarm thresholds are exceeded (or if oxygen levels fall below the set value). For optimum perception a two-tone alarm is used. Furthermore, Dräger Pac 7000 features an adjustable TWA alarm

and STEL alarm. A warning is likewise given at the end of the battery capacity or in the event of a device error.

Bump test mode

The safety of personnel must always have the first priority. Their safety depends on measurement and warning equipment functioning perfectly, which is why national regulations demand regular testing of equipment function using a known gas concentration. Dräger Pac 7000 is equipped with a bump test mode. When a bump test (function test or challenge test) needs to be performed, a notice icon appears on the screen. The bump test interval can be set by the user. The result of the bump test is saved in the

The instrument is equipped with an IR interface and can be linked to a PC via the connecting cradle or E-Cal system. Dräger Pac Vision or Dräger CC Vision software installed on the PC enables configuration of all functions, as well as calibration and download of the stored data.

Adjustable operating time

In addition, the instrument allows an individual operating time to be set (in days), e.g. a calibration interval, inspection interval or individual operating time end.

Data logger

Dräger Pac 7000 features a data logger in which all concentrations and events are stored together with their respective dates

DrägerSensors

New XXS sensors react particularly quickly

Large display

Clearly structured, scratch-proof display showing all information at a glance

Robust housing

Impact-resistance and ergonomic design



instrument's memory. Dräger Bump Test Station is available for easy performance of the bump test.

Calibration and configuration

Dräger Pac 7000 features a menu from which the bump test mode, fresh air calibration and span calibration can be selected. Access to fresh air and span calibration can be password-protected.

and times. The intervals at which peak concentrations are saved are variable and can be adjusted by the user. If a one-minute interval is set, the data logger has a capacity of about five days. The stored data can be downloaded via a PC and the installed Dräger Pac Vision or Dräger CC Vision software and edited using, for example, Microsoft® EXCEL® software or Dräger GasVision software.

Dräger Pac 7000 at a glance

- Gas inflow from top and front
- Unlimited instrument life
- Easy sensor replacement
- No-text display (no language problems)
- Continuous concentration display
- Visual alarm
- Audible alarm
- Vibration alarm
- Two adjustable alarm thresholds
- Adjustable TWA alarm
- Adjustable STEL alarm
- Display of peak concentration
- Battery pre- and main alarm
- Adjustable operating time with pre- and main alarm
- Adjustable bump test interval
- Adjustable bump test mode
- Password-protected menu for fresh air and sensitivity calibration
- IR interface
- Individual instrument configuration
- Replaceable battery
- Data logger

For further information, please visit:
www.draeger-safety.com/pac



ORDER INFORMATION

| Description | Measuring | Alarms | Alarms | Order-code |
|--|----------------|---------------------|---------------|------------|
| | | Threshold A 1 | Threshold A 2 | |
| Dräger Pac 7000 CO ¹⁾ | 0 to 1999 ppm | 30 ppm | 60 ppm | 83 18 673 |
| Dräger Pac 7000 CO ²⁾ | 0 to 1999 ppm | 35 ppm | 50 ppm | 83 18 970 |
| Dräger Pac 7000 CO | 0 to 1999 ppm | by customer request | | 83 18 676 |
| Dräger Pac 7000 H ₂ S ¹⁾ | 0 to 100 ppm | 10 ppm | 20 ppm | 83 18 674 |
| Dräger Pac 7000 H ₂ S ²⁾ | 0 to 100 ppm | 10 ppm | 20 ppm | 83 18 971 |
| Dräger Pac 7000 H ₂ S | 0 to 100 ppm | by customer request | | 83 18 677 |
| Dräger Pac 7000 O ₂ ¹⁾ | 0 to 25 Vol.-% | 19 Vol.-% | 23 Vol.-% | 83 18 675 |
| Dräger Pac 7000 O ₂ ²⁾ | 0 to 25 Vol.-% | 19.5 Vol.-% | 23.5 Vol.-% | 83 18 972 |
| Dräger Pac 7000 O ₂ | 0 to 25 Vol.-% | by customer request | | 83 18 678 |
| Dräger Pac 7000 CO ₂ | 0 to 5 Vol.-% | 0.5 Vol.-% | 3 Vol.-% | 83 18 975 |
| Dräger Pac 7000 Cl ₂ | 0 to 20 ppm | 0.5 ppm | 1 ppm | 83 18 978 |
| Dräger Pac 7000 HCN | 0 to 50 ppm | 10 ppm | 20 ppm | 83 18 973 |
| Dräger Pac 7000 NH ₃ | 0 to 300 ppm | 50 ppm | 100 ppm | 83 18 979 |
| Dräger Pac 7000 NO ₂ | 0 to 50 ppm | 5 ppm | 10 ppm | 83 18 977 |
| Dräger Pac 7000 PH ₃ | 0 to 20 ppm | 0.1 ppm | 0.2 ppm | 83 18 974 |
| Dräger Pac 7000 SO ₂ | 0 to 100 ppm | 1 ppm | 2 ppm | 83 18 976 |

¹⁾ Default configuration Europe

²⁾ Default configuration NAFTA

ACCESSORIES

| | |
|--|-----------|
| Connecting Cradle, complete with USB cable and Dräger Pac Vision software | 83 18 587 |
| Lithium battery | 45 43 808 |
| Dust and water filter | 45 43 836 |
| Leather carrying case | 45 43 822 |
| Dräger Bump Test Station, complete with test gas cylinder 58 L (gas type by customer request) | 83 18 586 |
| E-Cal instrument module for connection of 4 Dräger Pac 1000 to 7000 to a Dräger E-Cal Master Station or to Module Adapter | 83 18 589 |

Dräger Pac 7000:
Reliable in daily use.



Dräger Pac 7000:
High level of wearing comfort.

TECHNICAL DATA

| | | |
|------------------------|--|--|
| Dimensions (H x W x D) | 64 x 84 x 20 (battery compartment: 25) mm (2.5 x 3.3 x 0.8 in., battery compartment: 1 in.) | |
| Weight | 120 g (3.8 oz.) | |
| Ambient conditions | Temperature ¹⁾ | -30 to 50 °C (-20 to 120 °F) |
| | Pressure | 700 to 1300 hPa |
| | Humidity | 10 to 90 % r. h. |
| Ingress protection | IP 65 | |
| Display | Language-free LCD display, continuous indication of concentration, indication of concentration during alarm, peak concentration, TWA- and STEL-concentration, operating time, notice and warning functions | |
| Typical battery life | 3 years (O ₂ sensor 1.5 years) | |
| Acoustic alarm | Two-tone-alarm, typical > 90 dB (A) at a distance of 30 cm | |
| Data logger | Storage of concentration und events with date and time | |
| Approvals | CE-Sign (89/336/EEC, 94/9/EC) | |
| | ATEX | II 1 G EEx ia IIC, T4 I M 1 EEx ia I, T 4 |
| | UL | Class I, II, Div 1, Group A, B, C, D, E, F, G, Temp. Code T4 |
| | cUL | Class I, II, Div 1, Group A, B, C, D, E, F, G, Temp. Code T4 |
| | IECEX | EEx ia IIC, T4 |

¹⁾ Dräger Pac 7000 CO₂ -20 to 40 °C (-4 to 104 °F)
 Dräger Pac 7000 HCN -20 to 50 °C (-4 to 122 °F)
 Dräger Pac 7000 PH₃ -20 to 50 °C (-4 to 122 °F)



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.