

Dräger UCF 7000 Thermal Imaging Camera

Easy to use with one hand only. See more and make better decisions with optimal display options provided by the Dräger UCF 7000 thermal imaging camera. The camera is intrinsically safe (ATEX zone 1) and offers the maximum level of safety and reliability in potentially explosive atmospheres.



-
- User-friendly one-hand operation
 - Resolution of 160 x 120 pixel and 2x zoom integrated
 - "Application switch" - application-specific operating modes
 - „Snapshot“-Function
 - Integrated laser pointer
 - Integrated video- and soundrecording
 - Intrinsically safe: ATEX-approved for zone 1
-

MADE FOR PROFESSIONALS

Thermal imaging cameras by Dräger are valuable tools for orientation when fire, smoke, and darkness make navigation difficult. Designed to maintain your orientation to see where you are going as well as for finding persons or hotspots. Whether "indoor fire fighting" or "searching for a person" – various tasks can now be mastered optimally with the help of the new generation of Dräger UCF thermal imaging cameras.

The Dräger UCF 7000 provides a clear plus when it comes to safety and reliability, ease of use and decision making assistance for demanding firefighting jobs. The camera is equipped with innovative functions to meet and satisfy today's requirements

for professional search and rescue and firefighting personnel. And while the Dräger UCF 7000 is very easy to use, it also delivers excellent image quality. Application-specific displays provide more clarity and facilitate assessment of a situation.

COMFORTABLE ONE-HAND OPERATION

Using the Dräger UCF 7000 means one hand is always free: an invaluable plus and added freedom of movement for the user. The compact design and well-balanced low weight of only 1.4 kg (3 lbs) make the camera easy to operate with just one hand. The "application switch" makes it possible to use the camera safely and to utilize its functionality to the full extent even in highly stressful situations. A very sturdy attachable "crawling plate" permits



DRÄGER UCF 7000



the user to brace himself or herself on the ground without letting go of the camera. Also offering various carrying options for optimal carrying comfort.

BETTER OVERVIEW, MORE DETAILS

The Dräger UCF 7000 delivers excellent images to firefighters even if visibility is less than optimal. A resolution of 160 x 120 pixel as well as a 2x zoom provide a detailed impression of the situation. When the current image is always right in front of your eyes, rooms and the immediate vicinity are searched quickly and safely.

The risk of overlooking a detail is especially likely and a problem in difficult situations. Thanks to the "application switch" (application-specific operating modes), the Dräger UCF 7000 makes it possible to optimize the image display of the camera for the specific task at hand. For example, the camera's display can be optimized for finding persons or finding sources of fire.

One of three additional operating modes is quickly selected just by pressing a button:

- Fire (firefighting)
 - Persons (search and rescue)
 - ThermalScan (searching for hotspots)
- This additional selection provides firefighters with better insights in any situation.

EXTENDED FUNCTIONALITY

Optimized image processing provides a quicker overview in just seconds. The Dräger UCF 7000 even makes it possible to "see around corners" if the equipment limits the freedom of movement or the field of view. The "snapshot"-function is used to provide a temporary freeze-frame of thermal image, which can then be viewed on the display. This allows personnel to examine and check out even difficult to access areas quickly and safely.

The integrated laser pointer significantly simplifies pointing out the position of hazards – such as hotspots – to other team members and clearly defines the path of attack.

The Dräger UCF 7000 always offers a high temperature resolution – even in hot situations. This makes it possible to detect

cooler objects such as people even in the vicinity of a fire with best possible resolution. Integrated video- and sound recording functions as well as the ability to record single images are part of the Dräger UCF 7000 delivery scope.

EXTREMELY ROBUST

This camera is reliable even in the roughest and toughest environments and with the most demanding applications. Equipped with an almost indestructible housing, the Dräger UCF 7000 is heat-resistant and withstands usage-specific mechanical stresses with ease. Due to their high protection class of IP 67, Dräger UCF 7000 cameras are resistant to typical conditions encountered during an operation such as water and dust.

Modern lithium-ion battery technology yields operating times of up to four hours and provides users with the peace of mind needed during long runs.

EX PROTECTION FOR SAFETY

An explosive atmosphere may be prevalent especially for calls where there is no fire.

This means the equipment used must not be a source of ignition. The Dräger UCF 7000 is the tool of choice even in these types of situations. The device is intrinsically safe and approved for use in potentially explosive atmospheres including zone 1 according to ATEX.

STANDARD USB INTERFACE

The Dräger UCF 7000 is supplied with USB 2.0 interface by default, which makes it possible to configure the camera (e.g. setting an individual start image) and transfer the thermal image directly to a PC. Recorded images and video sequences

used for documentation purposes can also be transferred to a PC.

EXTENSIVE RANGE OF ACCESSORIES

The Dräger UCF 7000 is shipped complete with USB cable, attachable "crawling plate", and PC software CD.

ORDER INFORMATION

Dräger UCF 7000

Dräger UCF 7000 (50 Hz)	83 21 125
Accessories	
Transport case	83 21 099
Neck strap	83 23 031
Retractable lanyard	83 23 032
Hand support loop	83 23 033
Li-ion battery (with Ex-approval)	83 23 075
Battery charger	83 21 247
Power supply for charger	83 16 994
Vehicle Installation Kit (bracket and 12-30 V-cable)	83 21 253
Suction tripod, e.g. to mount on truck roof	83 23 070
Tripod	83 21 254
Universal clamp	83 21 259
12 V-adapter for operations with tripod	In preparation
12 V-power supply for operations with tripod	83 16 994

Included in scope of delivery

Thermal Imaging Camera with integrated laser pointer, "snapshot function", 2x zoom, 3 additional application modes ("Application switch"), e.g. ThermalScan and video-and sound recording, 1 battery and 1 charger. Add. with USB-cable, attachable crawling plate, PC-software, instructions for use and brief instruction.

TECHNICAL DATA

Dräger UCF 7000

Dimensions of camera (B x H x T)	125 x 280 x 110 mm
Weight	1.4 kg (3 lbs) incl. battery
Display	
Technology	Liquid crystal display (LCD)
Size (diagonal)	9 cm (3.5")
Application modes	Standard, Fire, Persons, ThermalScan
Housing	
Protection cover	Rubber material EPDM
Carrying loops	High-temperature resistant material
Housing material	High-temperature resistant plastic
Protection class	IP 67
Infrared-specifications	
Type of sensor	a-Si Microbolometer Array
Resolution	160 x 120 Pixel
IR spectral	7 to 14 µm
Temperature sensitivity	typically 0.035 °C (0.063 °F)
Picture frequency	50 Hz

Optics

Material	Germanium
Focus	From 1 m to infinity
Field of view	Horizontal: 47° / Vertical: 32° / Diagonal 62°

Operation

Operation time (at 23°C) with battery	typically 4 hours
Temperature measurement	Digital temperature display: -40 °C ... 1,000 °C (-40 °F ... 1832 °F)
Operating temperature	-40 °C ... 85 °C (-40 °F ... 185 °F) 150 °C (300 °F) for 20 minutes, 260 °C (500 °F) for 10 minutes
Battery technology	Rechargeable li-ion batteries
Battery Display	Precise 4-level battery indicator
Approvals	<p>The Dräger UCF 7000 meets the following explosion protection regulations:</p> <p>IEC 60079-0:2007 IEC 60079-11:2006 EN 60079-0:2009 EN 60079-11:2007 ANSI/ISA 12.12.01 CAN/CSA E60079-0 CAN/CSA E60079-11</p> <p>It is classified as follows:</p> <p>for Europe: I M2 / II 2G, Ex ib I Mb / Ex ib IIC T4 Gb for Australia: Ex ib IIC T4 Gb for the USA and Canada: Class I, Div. 2, Groups A, B, C, D, Class I, Zone 1, Ex ib IIC T4</p>
	Flame engulfment-test according to EN137:2006

┌

┐

└

┘



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.