

## Data Sheet

Mixing / Magnetic Stirrers



### color squid IKAMAG® white

The improved small magnetic stirrer now in new design.

new: Digital speed display (LED)

new: Electronically controlled motor for more capacity

new: Higher speed range from 0 - 2.500 rpm

new: Max. stirring quantity 1 l

- Outstanding chemical resistance due to glass top and synthetic bottom made of TPC-ET

- Recyclable materials

Accessories: IKAFLON® 15 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover, IKAFLON® 20 Magnetic stirring bar

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H <sub>2</sub> O) [l]	1
Stirring quantity max. (H <sub>2</sub> O) [l]	1
Motor rating input [W]	3
Motor rating output [W]	2
Speed display	LED
Speed range [rpm]	0 - 2500
Stirring bar length max. [mm]	30
Set-up plate dimensions [mm]	Ø 115
Dimensions (W x H x D) [mm]	145 x 45 x 160
Weight [kg]	0.54
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 54
RS 232 interface	no
Analog output	no
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	4
DC Voltage [V=]	12
Current consumption [mA]	300
Ident. No.	3671000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.