

Data Sheet

Mixing / Magnetic Stirrers



lab disc white

Ultra-flat compact magnetic stirrer, guaranteed with modern magnet coil technology. Wear-free drive with no moving parts. To ensure better mixing, the lab disc can reverse direction of rotation automatically every 30 seconds.

- High IP protection class (IP 65)
- Set-up plate and casing made from chemically resistant materials
- Slip-proof, safe stand

Accessories: IKAFLON® 15 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover, IKAFLON® 20 Magnetic stirring bar

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	0.8
Motor rating input [W]	5
Motor rating output [W]	3
Speed range [rpm]	15 - 1500
Stirring bar length max. [mm]	25
Set-up plate material	polyester
Set-up plate dimensions [mm]	Ø 100
Dimensions (W x H x D) [mm]	117 x 12 x 180
Weight [kg]	0.3
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 65
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	5
Ident. No.	3907500



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.