

Data Sheet Mixing / Shakers



Vortex 4 digital

Compact, universal small shaker suitable for shaking tasks with small vessels and microtiter plates.

- Wide range of attachments
- Attachment detection- Digital timer with countdown function
- Continuous or touch operation (with standard attachment)
- Two operating modes:

Mode A (safe mode with attachment detection)

the maximum speed of 3,000 rpm is only reached with the standard attachment in touch mode. When using other attachments the speed is limited to 1,300 rpm.

Mode B (without attachment detection)

a speed of 3,000 rpm is possible with all attachments.

- Stable in all speed ranges
- Sturdy zinc die cast casing

Accessories: MS 1.32 Test tube insert, MS 3.1 Standard attachment, MS 3.3 Universal attachment, MS 3.4 Microtiter attachment, MS 3.5 PCR plate attachment, MS 1.21 One-hand insert, MS 1.34 Test tube insert, MS 1.33 Test tube insert, MS 1.31 Test tube insert

| Technical Data | |
|--|--------------------------------|
| Type of movement | orbital |
| Shaker diameter [mm] | 4.5 |
| Permissible shaking weight (incl. attachment) [kg] | 0.5 |
| Motor rating input [W] | 10 |
| Motor rating output [W] | |
| Permissible ON time [%] | 100 |
| Speed min (adjustable) [rpm] | 200 |
| Speed range [rpm] | 0 - 3000 |
| Speed display | scale |
| Timer | yes |
| Timer display | 7 segment LED |
| Time setting range [min] | 1/60 - 999 |
| Operating mode | timer and continuous operation |
| Touch function | yes |
| Shaking table lock | no |
| Working with microtiter plates | yes |
| Number of microtiter plates | 1 |
| Dimensions (W x H x D) [mm] | 176 x 63 x 190 |
| Weight [kg] | 3 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| RS 232 interface | no |
| Analog output | no |
| Voltage [V] | 100 - 240 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 20 |
| DC Voltage [V=] | 24 |
| Current consumption [mA] | 800 |
| Ident. No. | 0004050100 |



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.

UK Office Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560 Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.