



# MET ONE 6000 Series Remote Airborne Particle Counters

High performing, reliable 0.3  $\mu\text{m}$  sensitivity remote

# The MET ONE counters high

## High performance

*0.3 µm sensitivity counter designed for ISO 21501 compliance for data accuracy and reliability*

## Easy to integrate with any FMS system

*Multiple communication options such as Pulse, Serial Modbus, Ethernet, Wireless and Analog*

## Long Life Laser™ diode

*Reduces the need for replacement parts and the overall cost of ownership*



Port Sizes	Model 6003	0.32 cm (1/8-inch) ID inlet	0.64 cm (1/4-inch) ID outlet
	Model 6005	0.32 cm (1/8-inch) ID inlet	0.64 cm (1/4-inch) ID outlet
	Model 6013	0.64 cm (1/4-inch) ID inlet	0.64 cm (1/4-inch) ID outlet
	Model 6015	0.64 cm (1/4-inch) ID inlet	0.64 cm (1/4-inch) ID outlet
Flow Rate	Model 6003	0.1 CFM (2.83 LPM)	
	Model 6005	0.1 CFM (2.83 LPM)	
	Model 6013	1.0 CFM (28.3 LPM)	
	Model 6015	1.0 CFM (28.3 LPM)	
Sensitivity	Model 6003	0.3 µm at 0.1 CFM (2.83 LPM)	
	Model 6005	0.5 µm at 0.1 CFM (2.83 LPM)	
	Model 6013	0.3 µm at 1.0 CFM (28.3 LPM)	
	Model 6015	0.5 µm at 1.0 CFM (28.3 LPM)	
Range	Model 6003	0.3 µm to 10.0 µm at 0.1 CFM (2.83 LPM)	
	Model 6005	0.5 µm to 10.0 µm at 0.1 CFM (2.83 LPM)	
	Model 6013	0.3 µm to 10.0 µm at 1.0 CFM (28.3 LPM)	
	Model 6015	0.5 µm to 10.0 µm at 1.0 CFM (28.3 LPM)	
Channel Sizes		STANDARD 2-CHANNEL	OPTIONAL 4-CHANNEL*
	Model 6003	0.3 and 0.5 µm	0.3, 0.5, 1.0 and 5.0 µm
	Model 6005	0.5 and 5.0 µm	0.5, 1.0, 5.0 and 10.0 µm
	Model 6013	0.3 and 0.5 µm	0.3, 0.5, 1.0 and 5.0 µm
Counting Efficiency	Model 6003	50% (± 20%) for 0.3 µm, (100% ± 10% at 1.5 times the minimum sensitivity). Fully complies with ISO21501-4.	
	Model 6005	50% (± 20%) for 0.5 µm, (100% ± 10% at 1.5 times the minimum sensitivity). Fully complies with ISO21501-4.	
	Model 6013	50% (± 20%) for 0.3 µm, (100% ± 10% at 1.5 times the minimum sensitivity). Fully complies with ISO21501-4.	
	Model 6015	50% (± 20%) for 0.5 µm, (100% ± 10% at 1.5 times the minimum sensitivity). Fully complies with ISO21501-4.	

\* Pulse models have two channels only

# MET ONE 6000 series of ISO 21501 compliant are the most reliable, top performing, high sensitivity remote particle counters



## ***Faster trouble shooting and reduced downtime***

*Instrument can be diagnosed for flow, sensor, communication failures, and count alarm or count alert through built-in or external status light*

## ***Easy installation options***

*Reduces initial installation cost and subsequent reinstallation cost during routine maintenance/calibration work*

## ***Built-in flow sensor***

*Improves operational reliability during continuous monitoring*

The MET ONE 6000 series remote airborne particle counter offers accurate and reliable continuous particle monitoring. With a sensitivity range of 0.3 or 0.5 to 10  $\mu\text{m}$ , data accuracy and repeatability through ISO 21501 compliant calibration, the MET ONE 6000 series is designed to meet the specific needs of cleanroom operations within the pharmaceutical, semiconductor, hard disk drive and flat panel display industries.

With an array of communication and mechanical installation options, the MET ONE 6000 is easy to integrate with any facility monitoring system. These features also reduce downtime for instrument removal and reinstallation during routine calibration and preventative maintenance cycles. Built with Long Life Laser™ technology, the MET ONE 6000 offers industry leading diagnostic features that reduce troubleshooting time and related downtime costs.



**LANGE** 

UNITED FOR WATER QUALITY

# Specifications

# HACH LANGE Services



Contact us to place an order, request information or receive technical support.



Service packages and extended warranty up to 5 years.



On site technical support.



Seminars and workshops: Practical and hands on training.




Regular customer information by post and email.



[www.particle.com](http://www.particle.com)  
Up to date and secure, with downloads, information and e-shop.

Light Source	Long Life Laser™ diode
Weight	0.82 kg (1.8 lbs)
Dimensions	13.56 w x 8.93 d x 12.06 h cm (5.34 x 3.52 x 4.75 inches)
Enclosure	304 stainless steel
Status Indicator	Multi-colored LED for normal status, count alarm, count alert, sensor failure, flow failure or communication failure
Power Requirements	9 to 28 VDC
Power Consumption	Serial and pulse units: 3.3 W; Ethernet unit: 4.3 W; Analog: 3.5 W; Wireless: 7.1 W. Maximum amperage requirement: 1 A
Operating Temperature	10 to 32 °C (50 to 90 °F), 5 to 95% relative humidity, non-condensing
Storage Temperature	-40 to 70 °C (-40 to 158 °F), 5 to 98% relative humidity, non-condensing
Signal Output Options	Pulse Analog 4–20 mA Serial RS-232 Serial RS-485 with Modbus RTU or FXB communication protocol Ethernet or Wireless with TCP/IP protocol At least 40.6 cm (16 inches) Hg
Vacuum Requirements	Standard 2 or Optional 4 (pulse units have 2 channels only)
Number of Size Channels	Through critical orifice
Flow Control	Model 6003/6005: 5% at 2,000,000 particles/ft <sup>3</sup> (70,600,000 particles/m <sup>3</sup> )
Coincidence Loss	Model 6013/6015: 5% at 400, 000 particle/ft <sup>3</sup> (14,000,000 particles/m <sup>3</sup> ) (except Pulse)
False Count Rate	One or less in five minutes
Accessories Included	DIN Rail Mounting Kit, Isokinetic Probe, Male Phoenix Terminal Strip with Cover, Operator Manual
How To Order	20886



## Optional Accessories\*\*\*

Optional 4-Channel Setting (Pulse models have two channels only)  
Wall Plate Mounting Kit  
Utility Terminal Box Mounting Kit  
Purge Filters, 1.0 CFM 1/4 Tube and 0.1 CFM 1/8 Tube  
Isokinetic Probes, 0.1 CFM and 1.0 CFM  
Cable, Service Port Connector with RS-232 Converter  
Relative Humidity/Temperature Probe  
Brackets, for RH/Temp Probe and LED Indicator Stack/Isokinetic Probe  
Remote Indicator Light Assembly  
Cable Assembly, 3 m for Remote Indicator Light Assembly  
Cable Assembly, RJ-45 Adapter  
Power Supply Unit, 24 VDC @ 5.0 A, Universal Input for FMS

\* If a serial I/O model is ordered, a second part number 2088600-232, 2088600-485, or 2088600-PLS must be ordered that will identify the serial I/O configuration as RS-485, RS-232, or Pulse, respectively.

\*\* Wireless models are available in limited number of countries. Contact your Hach sales representative for details.

\*\*\* For a comprehensive parts and accessories list, please refer to the user manual.





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.