

Product Data Sheet



A29

Safety Products



Description: Safety helmet with a versatile new shell design without rain trough. Complete with 30mm accessory slots and 4-point nylon web suspension with forehead comfort band and crown pad, 4-point chin strap anchorage and 3-level height adjustment. **Pinlock** adjustment headband offers a sturdy and easy use.







Materials: Shell – HDPE (High Density Polyethylene).
Temp. resistance : -30°C up to max 50°C
Electrical properties – 440 Vac

Weight: 347 gram

Standards: EN397

Size : 52-60cm

Accessories: Nomax sweatband
Penclip
Faceshields
Weldingshields
Ear defenders
Chinstraps (4point)

Standards characteristics	EN 397
Shock absorption	 M
Form and mass	 h Spherical M = 5 Kg
Free fall and shock angle	H = 1 m vertical
Maximum force	 F maximum 5 kN
Resistance to penetration	
Form and mass	 M Conical (60° C) M = 3 Kg
Free fall and shock angle	H = 1 m vertical
Number of shocks	 h 1 shock
Requirement	 No contact
Flame resistance	Flame 10 s at 5 cm
Requirement	No burn more than 5 s
Retention system strength	
Released force	150 N < F < 250 N
Ventilation area	If ventilation 150 < S < 450 mm²

End Shelf life : Shell max. 5 years after first of use.

Storage : Temp.: +5°C and max. +25°C.
Avoid direct sunlight.

Packaging: each in polybag.
20 helmets/Cse – LxWxH: 44.5x 31.8x 62.2cm – 08.39kg.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.