

Product Data Sheet



A29SPR

Safety Products



Description: Short-peak Safety helmet with 4 point nylon web suspension with forehead comfort band, 4 – point chin strap anchorage and 3-level height adjustment. The ratchet adjustment headband offers a firmer and more comfortable fit.
The 30mm accessory slots fits most available accessories.







Materials: Shell – HDPE (High Density Polyethylene).
Temp. resistance : -30 °C up to max +50°C
Electrical properties properties – 440Vac

Total Weight: 386 gram

Standards: EN397

Size : 52 – 60 cm.

Accessories : Nomaz sweatband
Penclip
Faceshields
Weldingshields
Ear defenders
Chinstraps (4-point).

Standards characteristics	EN 397	
Shock absorption		
Form and mass	h	Spherical M = 5 Kg
Free fall and shock angle		H = 1 m vertical
Maximum force		F maximum 5 kN
Resistance to penetration		
Form and mass		Conical (60° C) M = 3 Kg
Free fall and shock angle	h	H = 1 m vertical
Number of shocks		1 shock
Requirement		No contact
Flame resistance		Flame 10 s at 5 cm
Requirement		No burn more than 5 s
Retention system strength		
Released force		150 N < F < 250 N
Ventilation area		If ventilation 150 < S < 450 mm ²

End Shelf life: Shell max. 5 years after first date of use.

Storage : Temp : min.+5°C and max. +25°C. Avoid direct sunlight.

Packaging: each in polybag.
20 helmets/Cse – LxWxH: 44.5x 31.8x 62.2cm – 08.93kg.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.