

Product Data Sheet



Product image:



Product name:	AIRBELT
Part number:	150050 / 150051
Description:	The AIRBELT powered respirator is used for dust and particles only. The contaminated air is drawn through a dedicated P3 filter and supplies a continuous flow of clean air to the wearer's headpiece (hood or mask). The integral electronic control system continuously monitors the operation of the blower unit and provides a clear audible warning of any restriction in the air flow if below the permitted safety level. When using full face mask or airhood, the airflow is adjusted automatically as required.
Materials:	ABS
Weight:	950 gram
Dimensions:	LxWxH : 135 x 224 x 69 mm.
Standards:	EN 12941 for airhoods EN 12942 for masks
Notified Body:	0121
Airflow:	160 l/min airhood and 80 l/min mask, Electronically controlled.
Hose:	Length: 800mm. Diameter : 22 mm. Material: HDPE
Battery:	4,8 Volt – 4400 mAh. Type : NiMH (rechargeable).
Operating time	5 hrs (airhood) or 12 hrs (mask).
Charging time:	6 hrs. <i>The battery is supplied in an uncharged state.</i>
Application:	Welding, grinding, dust applications
Limits for use:	Do not use in confined spaces or places with a oxygen level <19%
Packaging:	Packed per piece in carton box: L x B x H : 425x215x135 mm



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.