

# Product Data Sheet



**Safety Products**

**Product image:**



**Product name:** CFR-1 Series - Reusable Particulate Respirators

**Part number:** Standard version 4200E/S and 4200E/M  
Welding version 4200EW/S and 4200EW/L

**Description:** The CFR-1 Series are elastomeric half-mask particulate filtering respirators having a replaceable formed filter element. Each facepiece is equipped with an exhalation valve.  
Each CFR-1 Respirator comes without filter element. P2 or P3 filter elements must be purchased separately.  
The CFR-1 is available as a Standard respirator (blue) and as a Welding respirator (gray). The Welding respirator has a stainless steel mesh front.

**Materials:** Face Seal: TPE based on hydrogenated isoprene  
Rigid Frame: Polypropylene  
Cover: Polypropylene  
Hook and Eye: Polypropylene  
Valves: EPDM (Ethylene Propylene Diene Rubber)  
Head Harness: Polypropylene  
Strap: Polyester with Spandex Elastic  
Filters: PP Filter media  
Welding front: Stainless steel mesh  
(Note: The CFR-1 contains no latex material.)

**Weight:** Standard version: 107 gram  
Welding version: 119 gram

**Sizes** Medium and Large

**Standards:** EN 1827: 1999 FM P2 / FM P3

**Protection factor** FMP2 = 12  
FMP3 = 50

**Notified Body:** CE 0158

**Application:** All dusty environments and welding / grinding applications where particulate protection is sufficient

**Limits for use:** Do not use in confined spaces or places with a oxygen level <19%

**Packaging:** Respirators packed per piece / Filters packed per 10

**Maintenance:** Other than daily cleaning no maintenance required



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.