

## TECHNICAL DATA SHEET



**PRODUCT NUMBER: CC890707X**  
**EASYCHEM 1A**

**Product Type:** Protective Clothing

**Range:** EasyChem

**Line:** Chemical Protection

**Brand:** Sperian

**Industry:** Hazmat suit for being used when the worker has to be protected in an accidental or short maintenance situation where to face unknown liquid or gaseous chemicals risks thanks to SCBA and the full suit.

### Benefits

- Resistant and durable by high frequency welding
- Air being exhaled at the inside of the suit for high contamination protection efficiency
- Comfortable thanks to heat stress reduction
- Light weight: 6 kg
- High protection factor through its supply breathing air and its magnetic valves: continuous overpressure protection
- Ergonomic and resistant boots: welded boots for higher safety
- Easy to change the gloves thanks to the special rings fixation
- SCBA encapsulated at the inside allows the use in highly risky environment avoiding the SCBA being contaminated.

### Technical Description

#### Description:

1. Comfortable gastight fully encapsulated suit with front gastight zip fastener from crotch to head protected by a flap. (EN-136 standard)
2. Wide back pocket for encapsulating the SCBA system consisting of one or two gaz cylinders bottles
3. Two single magnetic patented exhaust valves: one located on the breast and one on the top of the head
4. Safety boots (boots EN ISO 20345-2004-S5)
5. Hard wrist for gloves fixing covered by a flap for better protection and ease of use

#### Composition:

Raw material double-side coated polyester, with specific flame-retardant compound 650g/sqm  
Butyl Gloves (Powercoat 08010 butyl)  
PVC Boots

#### Color:

Suit: Orange  
Boots: White or Green

Gloves: Black (butyl)

## Size:

Suit: from S (1) to XL (4)

Safety boots: S (T40-41) – M (T42/43) – L (T44) – XL (T45-47)

Gloves: standard size: 9/9.5 - Also available: size 10/10.5

REFERENCE	HEIGHT (cm)	WAIST SIZE (cm)	CHEST SIZE (cm)
T=1 (S)	164-170	64-68	76-140
T=2 (M)	170-176	68-72	76-140
T=3 (L)	176-182	72-76	76-140
T=4 (XL)	182-188	76-80	76-140

**Gender:** Unisex

## Packaging:

Individually packed in a bag (including gloves, O-rings, adhesive roll and user instructions).

## Limitation of use:

HazMat clothing.

Suit can be used in temperatures of -30°C in +72°C. Never use the suit near fire or near heat sources.

## Warning:

Never disconnect the mask of the suit.

## Suit performances

### Chemical performances

EN374-3 (2004) Liquid permeation	Easychem 1a-F
Sodium hydroxide (50%)	Class 6/6
Sulfuric Acid (50%)	Class 6/6
Sulfuric Acid (98%)	Class 5/6
Fluorhydric Acid (70%)	Class 2/6
Chlorhydric Acid (37%)	Class 6/6
Phosphoric Acid (50%)	Class 6/6
Methanol	Class 4/6
Trichlorethylene	Class 1/6
Acetonitrile	Class 2/6
O-xylene	Class 2/6
Hexan	Class 3/6
Kerosene	Class 6/6
Sodium hypochlorite (14% chlorine)	Class 6/6

### Gloves performances

EN374.3 (2004) Liquid permeation	Butyl Gloves (black)
Sodium Hydroxide (50%)	Class 6/6
Acetone	Class 6/6
Ethyl Acetate	Class 4/6

### Mechanical resistances

Standards	Test-Resistance	Easychem 1a-F
NF EN ISO 7854: 12/97 Method B	Flex cracking	Class 5/6
NF EN ISO 7854: 12/97 Method B	Flex cracking at -30°C	Class 6/6
NF EN 863: 01/96	Puncture	Class 4/6
NF EN 530: 02/95 Method 2	Abrasion	Class 6/6
NF EN ISO 13934-1 (99)	R tensile strength Cross direction	Class 6/6
NF EN ISO 9073-4: 11/97	R tear T	Class 4/6
NF EN ISO 3071 (2006)	pH	Conform
NF EN ISO 3071 (2006)	pH	Conform
	Formol	Pass
EN 13 274-4: 2001 Method 3	Ignition/Flame	Conform
NF EN ISO 13934-1 (99)	Elongation at break Cross direction	29 %
NF EN ISO 13934-1 (99)	Elongation at break machine direction	25 %
NF EN ISO 9073-4: (97)	R tear M	71.2 N
NF EN ISO 13934-1 (99)	R tensile strength (machine direction)	2038 N

## Certification

**EC Category PPE:** 3\*

**Standards:**

**EN 943-1 (2003):** Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.

**Type 1a:** Performance requirements for ventilated and non-ventilated “gas-tight” chemical protective suits with a breathable air supply, e.g. a self-contained open-circuit compressed air breathing apparatus, worn **inside** the chemical protective suit.

**European Directives:**

89/686/EEC

**EC Certification Number:**

N° 0072/197/162/07/08/0083/EX01 08 09

**Quality Assurance:**

ISO 9001 / 2000

**The manufacturer or its legal representative supplier settled in the European Community:**

SPERIAN PROTECTION CLOTHING

**Delivered by:**

IFTH

Avenue Guy de Collongue

69134 Ecully Cedex

## Maintenance

**Storage Information:**

Keep equipment in the original packaging in a cool and dry place, not dusty, far from heat sources and far from direct light.

(+5°C/+45°C). Carefully follow the instruction on the label.

**Care Instructions:**

Be sure that the decontaminated and inspected suit was subjected to a test of pressure before putting back in service or in store.

\* PPE Category 3: Personal Protective Equipment with a design complex, designed to protect against the serious or fatal risks.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.