

TECHNICAL DATA SHEET



PRODUCT NUMBER: CC880 707X
EASYCHEM 1B

Product Type: Protective Clothing

Range: EasyChem

Line: Chemical Protection

Brand: Sperian

Activity domains: chemical, pharmaceutical, petrochemical, water treatment industries, fire-fighters brigades...

Industry: Hazmat suit for being used when the worker has to be protected in an accidental or short maintenance situation where to face unknown liquid or gaseous chemicals risks thanks to SCBA and the full suit.

Benefits

- Resistant and durable by high frequency welding
- Air being exhaled at the inside of the suit for high contamination protection efficiency
- Comfortable thanks to heat stress reduction (ventilation outside)
- Light weight: 6 kg
- High protection factor through its supply breathing air and its magnetic valves: continuous overpressure protection
- Ergonomic and resistant boots: welded boots for higher safety
- Easy to change the gloves thanks to the special rings fixation

Technical Description

Description:

1. Comfortable respiratory mask (Sperian panoramasque class 3 and compliant with EN-136 standard)
2. Zip fastener waterproof protected by a flap from crotch to head.
3. Two single magnetic patented exhaust valves: one located on the breast and one on the top of the head
4. Safety boots (boots EN ISO 20345 (2004) S5)
5. Hard wrist for gloves fixing

Composition:

Raw material double-side coated polyester, with specific flame-retardant compound 650g/sqm
Butyl Gloves (Powercoat 08010 butyl) or PVC Gloves (Deltasoft)
PVC Boots

Color:

Suit: Orange
Boots: White or Green
Gloves: Black (butyl) or Green (pvc)

Size:

Suit: from S (1) to XL (4)

Safety boots: S (T40-41) – M (T42/43) – L (T44) – XL (T45-47)

Gloves: standard size: 9/9.5 - Also available: size 10/10.5

REFERENCE	HEIGHT (cm)	WAIST SIZE (cm)	CHEST SIZE (cm)
T=1 (S)	164-170	64-68	76-140
T=2 (M)	170-176	68-72	76-140
T=3 (L)	176-182	72-76	76-140
T=4 (XL)	182-188	76-80	76-140

Gender: Unisex

Packaging:

Individually packed in a bag (including gloves, O-rings, adhesive roll and user instructions).

Limitation of use:

HazMat clothing.

Suit can be used in temperatures of -30°C in +72°C. Never use the suit near fire or near heat sources.

Warning:

Never disconnect the mask of the suit.

Suit performances

Chemical performances

EN374-3 (2004) Liquid permeation	Easychem 1a-F
Sodium hydroxide (50%)	Class 6/6
Sulfuric Acid (50%)	Class 6/6
Sulfuric Acid (98%)	Class 5/6
Fluorhydric Acid (70%)	Class 2/6
Chlorhydric Acid (37%)	Class 6/6
Phosphoric Acid (50%)	Class 6/6
Methanol	Class 4/6
Trichlorethylene	Class 1/6
Acetonitrile	Class 2/6
O-xylene	Class 2/6
Hexan	Class 3/6
Kerosene	Class 6/6
Sodium hypochlorite (14% chlorine)	Class 6/6

Gloves performances

EN374-3 (2004) Liquid permeation	Butyl Gloves (black)
Sodium Hydroxide (50%)	Class 6/6
Acetone	Class 6/6
Ethyl Acetate	Class 4/6

Mechanical resistances

Standards	Test-Resistance	Easychem 1a-F
NF EN ISO 7854: 12/97 Method B	Flex cracking	Class 5/6
NF EN ISO 7854: 12/97 Method B	Flex cracking at -30°C	Class 6/6
NF EN 863: 01/96	Puncture	Class 4/6
NF EN 530: 02/95 Method 2	Abrasion	Class 6/6
NF EN ISO 13934-1 (99)	R tensile strength Cross direction	Class 6/6
NF EN ISO 9073-4: 11/97	R tear T	Class 4/6
NF EN ISO 3071 (2006)	pH	Conform
NF EN ISO 3071 (2006)	pH	Conform
	Formol	Pass
EN 13 274-4: 2001 Method 3	Ignition/Flame	Conform
NF EN ISO 13934-1 (99)	Elongation at break Cross direction	29 %
NF EN ISO 13934-1 (99)	Elongation at break machine direction	25 %
NF EN ISO 9073-4: (97)	R tear M	71.2 N
NF EN ISO 13934-1 (99)	R tensile strength (machine direction)	2038 N

Certification

EC Category PPE: 3*

Standards:

EN 943-1 (2003): Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.

Type 1b: Performance requirements for ventilated and non-ventilated “gas-tight” chemical protective suits with a breathable air supply, e.g. a self-contained open-circuit compressed air breathing apparatus, worn outside the chemical protective suit

European Directives:

89/686/EEC

EC Certification Number:

N° 0072/197/162/07/08/0083

Quality Assurance:

ISO 9001 / 2000

The manufacturer or its legal representative supplier settled in the European Community:

SPERIAN PROTECTION CLOTHING

Delivered by:

IFTH
Avenue Guy de Collongue
69134 Ecully Cedex

Maintenance

Storage Information:

Keep equipment in the original packaging in a cool and dry place, not dusty, far from heat sources and far from direct light.
(+5°C/+45°C). Carefully follow the instruction on the label.

Care Instructions:

Be sure that the decontaminated and inspected suit was subjected to a test of pressure before putting back in service or in store.

* PPE Category 3: Personal Protective Equipment with a design complex, designed to protect against the serious or fatal risks.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.