

pulsar *nova*[™]

Six new generation
sound level meters that
are out of this world!



 **pulsar**
Instruments Plc

Industrial, Occupational and Environmental noise measurement products.

+44 (0)1723 518011
www.pulsarinstruments.com

The Pulsar Nova Range

A range of six new generation sound level meters to suit every application & budget

- Compliant with IEC 61672-1:2002
- Intuitive design
- High performance
- Simple to use
- Designed and manufactured in the UK
- Rugged metal case
- Large anti-glare display
- High definition colour OLED display
- Greater than 30 hour battery life
- 4GB removable memory card
- Dynamic range of 20dB(A) to 140dB(A) & 143dB(C)
- Simultaneous measurement of all key parameters
- Unique calibration prompt
- Standard and advanced data viewing modes
- Optional features to cover every requirement & budget



nova™

+44 (0) 1723 518011
www.pulsarinstruments.com

Overview

The Nova range of high performance sound level meters successfully combines advanced technology noise measurement methods with ease of use and durability.

We have listened to our customers for over 40 years. We know that you all have different requirements and what you need today may change in the future. We also understand that purchasing noise measurement equipment is a huge investment.

The Nova range consists of six powerful sound level meters. These differ from other sound level meters, as they offer the user the unique opportunity to add features either immediately or at a later date so that the instrument will always be suitable for their requirements.

Standard Measurement Kits

Instruments are usually supplied as part of a noise measurement kit which contains everything required to take noise measurements.

The Nova kit contains:

Nova sound level meter, acoustic calibrator, windshield, batteries, hard kit case, 7 year warranty, calibration certificates, the Pulsar AnalyzerPlus software and download cable.

Outdoor Measurement Kits

Both Class 1 and Class 2 instruments have a removable preamplifier which enables the instruments to be used with microphone extension cables. These outdoor measurement kits transform the hand held instrument into a longer term, outdoor monitoring system.

Software

AnalyzerPlus allows the user to download their measurement data onto a PC or laptop for analysis and to create a variety of reports.

Nova series features table

	Class 1	Class 2	SPL	Simultaneous A, C & Z Frequency Weightings	Simultaneous F.S & 1/Time Weightings	Leq/Peak (inc C-A & Quick Integrator Settings)	Pause & Back Erase	Data Logging	Manual Audio Record & Data Logging	Audio Note & Data Logging	Repeat Timer & Data Logging	Single Timer	TWA/dose	Ln Values	1:1 Octaves
Model 41	✓		✓	✓	✓	○	○	○	○	○	○	○	○	○	○
Model 42		✓	✓	✓	✓	○	○	○	○	○	○	○	○	○	○
Model 43	✓		✓	✓	✓	✓	✓	○	○	○	○	○	○	○	○
Model 44		✓	✓	✓	✓	✓	✓	○	○	○	○	○	○	○	○
Model 45	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Model 46		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

✓ Standard feature ○ Optional add on feature

Model 41 (Class 1) & Model 42 (Class 2)

Entry level sound level meter



- IEC 61672-1:2002 compliant sound level meters
- Low cost Class 1 or Class 2 SPL instruments
- OLED display can be seen in all conditions
- Calibration prompt for compliant, accurate measurements
- Simultaneous measurement of all key noise parameters
- Add features now or later so that your meter always suits your budget and needs
- 20dB(A) to 140dB(A) dynamic measurement range

Applications

- Basic noise level assessments
- Emergency service alarm testing
- Sound system installation
- Vehicle noise measurement

Optional features table

	Class 1	Class 2	SPL	Simultaneous A, C & Z Frequency Weightings	Simultaneous F S & I Time Weightings	Leq/Peak (inc C-A & Quick Integrator Settings)	Pause & Back Erase	Data Logging	Manual Audio Record & Data Logging	Audio Note & Data Logging	Repeat Timer & Data Logging	Single Timer	TWA/dose	Ln Values	1:1 Octaves
Model 41	✓		✓	✓	○	○	○	○	○	○	○	○	○	○	○
Model 42		✓	✓	✓	○	○	○	○	○	○	○	○	○	○	○

✓ Standard feature ○ Optional add on feature

Model 43 (Class 1) & Model 44 (Class 2)

The professional's sound level meter



- A simple to use occupational sound level meter
- All of the features of the Model 41 & Model 42 with the addition of:
- Leq, Peak and C-A for the HML method of hearing protection calculation
- Pause & back erase function
- 20dB(A) to 140dB(A) & 143dB(C) dynamic measurement range
- Colour coding for measurement status

Applications

- Noise at work
- Occupational & industrial hygiene
- Construction noise measurement
- Machinery noise testing
- Entertainment noise measurement



Optional features table

	Class 1	Class 2	SPL	Simultaneous A, C & Z Frequency Weightings	Simultaneous F S & I Time Weightings	Leq/Peak (inc C-A & Quick Integrator Settings)	Pause & Back Erase	Data Logging	Manual Audio Record & Data Logging	Audio Note & Data Logging	Repeat Timer & Data Logging	Single Timer	TWA/dose	Ln Values	1:1 Octaves
Model 43	✓	○	✓	✓	✓	✓	✓	○	○	○	○	○	○	○	○
Model 44	○	✓	✓	✓	✓	✓	✓	○	○	○	○	○	○	○	○

✓ Standard feature ○ Optional add on feature

Model 45 (Class 1) & Model 46 (Class 2)

The premium sound level meter

All of the features of the Model 43 & Model 44 with every feature below as standard:

- AnalyzerPlus data-logging software
- Manual audio record
- Audio Note
- Repeat Timer
- Single Timer
- TWA/dose
- Ln Values
- Real time 1:1 octave band filters

Applications

- Noise at work
- Occupational & industrial hygiene
- Environmental noise measurement
- Boundary noise measurement
- Machinery noise testing
- Vehicle noise testing
- Entertainment noise measurement



Features table

	Class 1	Class 2	SPL	Simultaneous A, C & Z Frequency Weightings	Simultaneous FS & I Time Weightings	Leq/Peak (inc C-A & Quick Integrator Settings)	Pause & Back Erase	Data Logging	Manual Audio Record & Data Logging	Audio Note & Data Logging	Repeat Timer & Data Logging	Single Timer	TWA/dose	Ln Values	1:1 Octaves
Model 45	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Model 46		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

General

Accuracy

Class 1 – Model 41, Model 43, Model 45
Class 2 – Model 42, Model 44, Model 46

Applicable Standards

IEC 61672-1:2002 Class 1 or Class 2, Group X
IEC 60651:2001 Type 1 I or Type 2 I
IEC 60804:2000 Type 1 or Type 2
IEC 61252:1993 Personal Sound Exposure Meters
ANSI S1.4 -1983 (R2006), ANSI S1.43 - 1997 (R2007)
ANSI S1.25:1991
1:1 Octave Band Filters to IEC 61260 & ANSI S1.11-2004

Microphone

Class 1 PM1 pre-polarized
Class 2 PM2 pre-polarized

Microphone Preamplifier

PA40 Removable Preamplifier

Measurement Range

20dB - 140dB RMS Single Range (143dB peak)

Noise Floor

<18dB(A) Class 1, <21dB(A) Class 2

Time Weightings

'F' (Fast), 'S' (Slow) & 'I' (Impulse) all measured simultaneously

Frequency Weightings

RMS & Peak: A, C, & Z (un-weighted) all measured simultaneously

Frequency Bands

10 1:1 Octave Bands: 31.5Hz to 16kHz

Integrators

Three simultaneously measuring "virtual" noise meters.

Integrator 1 is preset to Q3 for Leq functions.

Integrators 2 & 3 can be configured with the following:

Exchange Rate: 3, 4 or 5dB

Threshold: 70dB to 120dB (1dB steps)

Time Weighting: None or Slow

Criterion Level: 70dB to 120dB (1dB steps)

Criterion Time: 1 to 12 hours in 1 hour steps

Integrator Quick settings (pre-set)

EU, OSHA HC & OSHA NC, OSHA HC & ACGIH, MSHA HC & MSHA EC, Custom 1 & Custom 2

Ln Statistical Values

14 independent statistical Ln values calculated from 1/16th LAF

7 are preset to L1.0, L5.0, L10.0, L50.0, L90.0, L95.0 & L99.0

7 user defined Ln values

Time History Data Rates (Global settings)

10ms, 62.5ms, 125ms, 250ms, 1/2 sec, 1 sec, 2 sec (user selectable)

Language options

English, French, German, Italian, Spanish as standard

NB. Other language options will be available.

Physical

Batteries

6 x AA

Battery life

Typically 30 hours with Alkaline AA
Typically 50 hours with Lithium AA
Rechargeable battery life is dependent upon the battery type and screen brightness

External power

5v-15v via Multipin I/O socket

Weight

440g without batteries

Size

280mm x 80mm x 42mm with preamp and microphone

Connections

USB 2.0 Mini-B to PC

AC output via 3.5mm Stereo jack

AC & DC output via Multipin I/O socket

Tripod Mount

1/4" Whitworth socket

Case

Die cast aluminium with silicon elastomer

keypad and soft touch back

Display

High resolution anti-glare OLED display

Ambient light sensor

Illuminated keypad

Supplied Accessories

Windshield, Wrist Strap, USB Download Cable, AnalyzerPlus software, AA Batteries

Conformance, Logging & Storage

Conformance

Environmental

Operating Temperature: -10°C to +50°C
Storage Temperature: -20°C to +60°C

Humidity: Up to 95% RH Non-Condensing

Electromagnetic performance

IEC 61672-1:2002 & IEC 61672-2:2003

Except where modified by EN 61000-6-1:2007 & EN 61000-6-1:2007

Logging and Storage

Memory

4GB removable memory card

Audio Note Recording

A spoken note (up to 30 seconds) attached to measurements

Audio Recording

Manual recording

User options:

Studio quality - 96kHz/32bit WAV format

Standard quality - 16kHz/16bit WAV format

Measurement Control

The unit can be set to record and store data over fixed times of:

1 min, 5 min, 10 min, 15 min, 30 mins, 1 hour, Lden (Day, Evening, Night)

Automatic Synchronisation & Repeat options

Pause

Back Erase with user selectable duration (via AnalyzerPlus software)

Model Specific Measurement Parameters

Standard Measurement Parameters

Model 41 & Model 42:

Lxy, Lxy Max, Lxy Min

Time, date & duration of measurement

Extra measurement and stored functions available.

Standard Measurement Parameters Model 43 & Model 44:

Lxy, Lxy Max, Lxy Min

Lx_{eq}, LC_{Peak}, LZ_{Peak}, LAP_{Peak}, LC_{eq}-LA_{eq}, Lx_E, LA_{leq}

Graph of Short LA_{eq}, LC_{Peak}

Time, date & duration of measurement

Extra measurement and stored functions available.

Standard Measurement Parameters Model 45 & Model 46:

Lxy, Lxy Max, Lxy Min

Lx_{eq}, LC_{Peak}, LZ_{Peak}, LAP_{Peak}, LC_{eq}-LA_{eq}, Lx_E, LA_{leq}

Graph of Short LA_{eq}, LC_{Peak}

Measurement Run Time

Integrators 2 & 3: TWA, Dose %, Est Dose %

Real-Time 1:1 Octave Bands (Graphical & Numeric)

14 Statistical Values (Ln)

Stored Parameters

- Model 45 & Model 46

LxyMax & Time History of LxyMax

LA_{eq}, LC_{eq}, LZ_{eq}, LC_{Peak}, LZ_{Peak}, LAP_{Peak}, LA_{leq}

Time History of LA_{eq}, LC_{eq}, LZ_{eq}, LC_{Peak}, LZ_{Peak}, LAP_{Peak}, LA_{leq}

Integrators 2 & 3: LAVG, TWA, % Dose

Time History of LAVG

1:1 Octave Bands: Overall Leq & Leq Time

History for each band

Ln Values: 14 independent statistical values

Audio recording during measurement

Time, date & duration of measurement

Where x means the three frequency weightings A, C and Z and y means the three time weightings 'S' (Slow), 'F' (Fast) and 'I' (Impulse). All weightings simultaneously measured where appropriate.

Other functions may be calculated by the AnalyzerPlus software.

Useful Information

Input & Output Cables

PSR101 - Nova 1m Mini-B to Type A USB Cable

PSR171 - Nova power input cable, 2.1mm Power Jack, 2m

PSR174 - Nova AC & DC Output, 18 way to 2 x Phono, 1m

PSR176 - Nova 12v Battery pack cable 2m to tinned ends with inline fuse

PSR177 - Nova AC output cable, 3.5mm Mono to 3.5mm Stereo Jack, 2m

PSR185 - Nova AC output cable, 18 way to Phono, 1m

PSR190 - Nova power input cable, 2.1mm Power Jack & mains power supply

Software

AnalyzerPlus Download, Configuration & Analysis software supplied as standard.

Compatible with Microsoft Windows XP, Vista, 7 (32bit & 64bit) & 8 (32bit & 64bit)

Ordering Codes

Sound Level Meter and Measurement Kit

Model 41: PSR-41

Model 41 Kit: PSR-41K

Model 42: PSR-42

Model 42 Kit: PSR-42K

Model 43: PSR-43

Model 43 Kit: PSR-43K

Model 44: PSR-44

Model 44 Kit: PSR-44K

Model 45: PSR-45

Model 45 Kit: PSR-45K

Model 46: PSR-46

Model 46 Kit: PSR-46K

Measurement Kits

Instruments can be supplied as a complete measurement kit to ensure that you have all the accessories necessary to perform your noise survey.

The Nova noise measurement kit contains: Sound Level Meter, Acoustic Calibrator, Windshield, Kit case, Wrist Strap, AnalyzerPlus Software, USB Download Cable, Batteries, Operating Manuals, Calibration Certificates & 7 year Warranty.

Options Ordering Codes

- Model 41 & Model 42

PSR0110 - Data Logging

PSR0111 - Manual audio record & Data Logging

PSR0112 - Audio Note & Data Logging

PSR0113 - Repeat Timer & Data Logging

PSR012 - Single Timer

PSR013 - Leq/Peak & C-A

PSR014 - Pause / Back erase

PSR015 - TWA/ dose

PSR016 - Ln Values

PSR017 - Real Time 1:1 octave band filters

Options Ordering Codes

- Model 43 & Model 44

PSR0110 - Data Logging

PSR0111 - Manual audio record & Data Logging

PSR0112 - Audio Note & Data Logging

PSR0113 - Repeat Timer & Data Logging

PSR012 - Single Timer

PSR015 - TWA/dose

PSR016 - Ln Values

PSR017 - Real Time 1:1 octave band filters

Notes: All specifications, features and values are subject to change.

Your Pulsar Distributor:



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.