## RIKEN

# **PORTABLE OXYGEN MONITOR**



### **MODEL**

0 < 0 7

JML approved (Japanese Ministry of Labor) ATEX·IECEx approved



#### **Features**

- Intrinsically safe ExialICT3
- Extension cable available (5m standard, 10m, 20m and 30m)
- Maximum 5000 hours of continuous operation by 2 "AA" alkaline dry cells
- Impact resistant protective rubber boot
- Large LCD display with auto backlight
- Audible/visual/vibration alarms
- Compact and light weight
- 66W × 114H × 33D mm, 230g only









### PORTABLE OXYGEN MONITOR MODEL OX-07

#### **Specifications**

Туре	Type A	Туре В
Gas detected	Oxygen in air	
Detection principle	Galvanic cell	
Detection range (Increments)	0.0-40.0%vol. (0.1%vol.)	
Alarm set point	Low alarm 19.5%vol. High alarm 23.5%vol. Over 40.0%vol.	No alarm
Trouble alarm	Sensor disconnection, low battery, circuit failure, calibration range error	
Alarm types	Gas alarm : flashing light, intermittent buzzer and flashing gas value, pulsing vibration	No alarm
	Trouble alarm : flashing light, intermittent buzzer and Display of error message	
Display	Digital display	
Power source	Alkaline dry cells (2-AA size), 2pcs	
Continuous operation	Maximum 5000 hours (at 25°C, and no alarm, no backlight)	
Safety design	Intrinsically safe (ExialICT3)	
Operating temp. & humidity	-20℃~+50℃: Humidity below 95%RH (non-condensing)	
Special functions	Manual backlight for LCD (automatically lit during alarm) Peak hold (maximum and minimum)	
Dimensions & weight	Approx. 66(W)×114(H)×33(D)mm Approx. 230g (Instrument only)	
Standard accessories	Hand strap	
Optional accessories	Extension cable 5m, 10m, 20m, 30m, Carrying case	



#### Standard accessories



Hand strap

#### Optional accessories







Carrying case



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.

**:::** UK Office Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399 Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.