



Refrigerated Baths

These baths are a complete refrigerated circulating system for open or closed applications for temperature ranges from -35°C to 100°C. Each bath is supplied with a lid and bridging plate.

There are three bath capacities: 7 litre (RB-5A), 12 litre (RB-12A) and 22 litre (RB-22A). Temperature control is via one of the four thermoregulators and together they offer a choice of 12 different bath combinations.

- Circulating bath with built in refrigeration
- Temperature range from -35°C to 100°C
- Three different capacities of refrigerated bath; 7, 12 or 22 litre
- The combination of 3 circulating baths and 4 thermoregulators provides 12 options

Technical Specification

Cooling (at 20°C ambient)	RB-5A	RB-12A	RB-22A
Minimum achievable temperature ¹	-20°C	-35°C	-30°C
Cooling capacity at 20°C	145W	240W	240W
Cooling capacity at 0°C	145W	240W	240W
Cooling capacity at -10°C	110W	230W	220W
Dimensions			
Overall Size - L x W x H (mm) ²	430 x 250 x 566	430 x 370 x 610	430 x 395 x 565
Liquid surface to top of bath - max (mm)	65	65	65
Internal dimensions - L x W x H (mm)	192 x 151 x 200	208 x 300 x 150	360 x 295 x 220
Working length to thermoregulator (mm)	224	224	250
Working depth - max/min (mm)	180/135	130/85	200/160
Working capacity - max/min (litres)	7.0/5.5	11.6/9.6	22/18
Shipping weight kg ³	31	53	61

¹ Using a mixture of 50% of water and 50% antifreeze to achieve -20°C.

Alternatively 40% water, 40% antifreeze, 20% alcohol to achieve -35°C.

² Overall size with controller

³ Add thermoregulator and bath shipping weight to get shipping weight of complete bath system.

Ordering Information

Product Code	Description
FRB5D	RB-5A bath, 7 litre capacity with built in refrigeration unit, -20°C to 100°C
FRB2D	RB-12A bath, 12 litre capacity with built in refrigeration unit, -35°C to 100°C
FRB22D	RB-22A bath, 22 litre capacity with built in refrigeration unit, -30°C to 100°C



RB-12A



RB-5A



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.